6GT20020JE50

Industrial automation components

Add to quote

Ask about this product



Manufacturer	Siemens
Catalog number	6gt20020je50
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Product ID	6GT2002-0JE50
AL Field	N
Compliance	Produkt zgdony z RoHS od: 31.01.2019
Configurable Product	False
Country of Origin	DE
ECCN	9N9999
ETIM 7	EC001604
Group Classification Key	R322
List of Characteristics	ID10.M
Packaging Size	MM
Product Description	RFID communication module RF186CI for Profinet, Ethernet, EtherNet/IP, 2 readers connectable, DI/DO interface
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Customs Tariff Code	85176200
EAN	4047623410133.0
eClass 6	27-24-26-08
eClass 7.1	27-24-26-08

Automation Trader
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

Phone
+44 7418 359 399

Email
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.

eClass 8	27-24-26-08
eClass Version 9	27-24-26-08
eClass Version 9.1	27-24-26-08
Quantity in Package	1
Packaging Length	182,00
Packaging Width	90,00
Packaging Height	50,00
Product Code	9470
Comparative Metals Coefficient	31.01.2019
UPC	804766933257.0
Weight	301 kg

Description

The Siemens 6GT20020JE50 is an RFID communication module designed for seamless integration into PROFINET and Ethernet networks. This module supports both PROFINET IO and EtherNet/IP protocols, enabling versatile communication options. It accommodates up to two RFID readers, facilitating efficient data acquisition in industrial settings. The device features a DI/DO interface, allowing for straightforward integration with digital input and output systems. Constructed with thermoplastic (Valox 467, fiberglass reinforced) housing, it ensures durability and reliability in demanding environments. The module operates within a temperature range of -25°C to +55°C, suitable for various industrial applications. With an IP67 protection class, it offers robust resistance against dust and water ingress, making it ideal for harsh conditions. The device is CE, FCC, and cULus certified, meeting international standards for safety and electromagnetic compatibility. Its compact dimensions and lightweight design—measuring 60 mm in width, 45 mm in height, and 165 mm in depth, with a net weight of 0.26 kg—allow for flexible installation options. The Siemens 6GT20020JE50 is a reliable solution for integrating RFID technology into industrial automation systems, enhancing operational efficiency and data management capabilities.