Meter Centers

Surface Mount Meter Mains, 1-Phase, 3-Wire 120/240V AC

Selection

- UL listed
- Pad locking provisions on all devices
- Horn bypass and 5th jaw available as noted
- Side hinged door with one screw removal where shown
- Suitable for use only as service entrance equipment
- Contact local utility to confirm meter socket placement prior to installation
- See end of section for dimensions and wiring diagrams

MM0202ML1100S



100A meter main (field added), OH feed only

MM0202ML1125H



125A meter main (field added)

MM0202B1XXXRJBX



125, 150, and 200A meter main (factory installed), side hinge door.

MM0406L1200X



200A meter main (field added), side hinge door

MM0202BXXX



125 and 200A meter mains, side hinge door

MM0404L1400RLM



400A meter main, side hinge door, provisions for two field installed mains

Overhead/Underground 1-Phase, 3-Wire SN

Meter Main Combinations				UL: Overhead/ Underground	EUSERC: Overhead/ Underground	Short Circuit Rating	Catalog Number	Hub Provision	5th Jaw	Dimensions (inches)			Cover Type	List Price $	Foot Notes
Ampere Rating	Main Breaker	No. of Spaces	No. of Circuits							Height	Width	Depth			
Main Breaker Field Installed															
100	QP	2	2	OH	OH	10,000	**MM0202ML1100S**	RX	EC5J	18.00	7.375	4.00	Ring	**366.00**	1
125	QP	2	2	OH	OH	22,000	**MM0202ML1125H**	2-RX	EC5J	17.00	16.00	5.00	Ring	**498.00**	
200	1-QN/2-QP	4	6	OH/UG	OH	22,000	**MM0406L1200H**	2-RX	EMC5J	19.75	17.125	5.00	Ring	**965.00**	
200	1-QN/2-QP	4	6	OH/UG	—	22,000	**MM0406L1200RH**	2-RX	EMC5J	19.75	17.125	5.00	Ringless	**996.00**	
200	1-QN/2-QP	4	6	OH/UG	—	22,000	**MM0406L1200RHJB**	2-RX	Installed	19.75	17.125	5.00	Ringless	**1030.00**	2
400	(2) QN(R), QN(R)H, QP, QPH	2	2	OH/UG	—	22,000	**MM0404L1400RLM**	HD	S35815-2	29.00	27.00	6.00	Ringless	**2923.00**	3
Main Breaker Factory Installed															
125	Q2125H	2	2	OH/UG	—	22,000	**MM0202B1125RJB**	RX	Installed	17.00	16.00	5.00	Ringless	**1752.00**	2
150	QN2150H	2	2	OH/UG	—	22,000	**MM0202B1150RJB**	RX	Installed	17.00	16.00	5.00	Ringless	**1752.00**	2
150	QN2150H	2	2	OH/UG	OH	22,000	**MM0202B1150**	RX	EMC5J	17.00	16.00	5.00	Ring	**1736.00**	
150 NEW	QN2150H	2	2	OH/UG	—	22,000	**MM0202B1150R**	RX	EMC5J	17.00	16.00	5.00	Ringless	**1736.00**	
200	QN2200H	2	2	OH/UG	OH	22,000	**MM0202B1200**	RX	EMC5J	17.00	16.00	5.00	Ring	**1752.00**	
200	QN2200H	2	2	OH/UG	—	22,000	**MM0202B1200R**	RX	EMC5J	17.00	16.00	5.00	Ringless	**1736.00**	
200	QN2200H	2	2	OH/UG	—	22,000	**MM0202B1200RJB**	RX	Installed	17.00	16.00	5.00	Ringless	**1752.00**	2
125	Q2125H	2	2	OH/UG	OH/UG	22,000	**MM0202B1125RJBX**	RX	Installed	17.00	18.42	5.14	Ringless	**1752.00**	2, 3
150	QN2150H	2	2	OH/UG	OH/UG	22,000	**MM0202B1150RJBX**	RX	Installed	17.00	18.42	5.14	Ringless	**1752.00**	2, 3
200	QN2200H	2	2	OH/UG	OH/UG	22,000	**MM0202B1200RJBX**	RX	Installed	17.00	18.42	5.14	Ringless	**1752.00**	2, 3

For inches / millimeters conversion, see Application Data section.

Listed by Underwriters' Laboratories, Inc., under file #E10703 vol. 1.

① Shipped standard with two units per carton. Each unit supplied with 1.25" hub.
② Device has horn bypass.
③ Devices with "X" suffix include an extra wide utility section.

Meter Centers NEW

Surface Mount Meter Load Centers, 1-Phase, 3-Wire 120/240V AC 150-200A *Selection*

- UL listed
- Overhead and underground feed applications
- Underground feed accomplished by use of removable gutter trough
- Load wires bottom or back exit only
- 22,000 AIC rated
- Pad locking provisions on all devices
- Side hinge doors removable by backing out only one screw
- Suitable for use only as service entrance equipment
- RX type hub provision on top end wall
- HC type hub provision on bottom end wall
- Field addable 5th Jaw (EC5J2)
- Contact local utility to confirm meter socket placement prior to installation
- See end of section for dimensions and wiring diagrams



MC0606L1200R (Shown)
MC0606L1200RJB
MC0606L1200RA



200A, main lug, 6 circuit (Twelve 1" spaces), for use with up to six 2-pole breakers

MC0408B1150T (Shown)
MC0408B1200T
MC0408B1150RT
MC0408B1200RT



150 or 200A, main breaker, four 1" spaces, feed thru lugs provided

MC0816B1150CT (Shown)
MC0816B1200CT
MC0816B1150RCT
MC0816B1200RCT



150 or 200A, main breaker, eight 1" spaces, feed thru lugs provided

MC2040B1150RC (Shown)
MC2040B1200RC
MC2040B1150RJBC
MC2040B1200RJBC



150 or 200A, main breaker, twenty 1" spaces provided

Ampere Rating	Main Breaker	No. of Spaces	No. of Circuits	Catalog Number	Replaced Catalog Number	Dimensions			Cover Type	List Price $	Notes
						Height	Width	Depth			
150	MBK150	4	8	**MC0408B1150T**	**MC0408MB1150T**	30.0	14.0	5.0	Ring	**1318.00**	3
150	MBK150	4	8	**MC0408B1150RT**	**MC0408MB1150RT**	30.0	14.0	5.0	Ringless	**1318.00**	3
150	MBK150	8	16	**MC0816B1150CT**	—	32.0	14.0	5.0	Ring	**1387.00**	3
150	MBK150	8	16	**MC0816B1150RCT**	—	32.0	14.0	5.0	Ringless	**1387.00**	3
150	MBK150	20	40	**MC2040B1150RC**	**MC2040MB1150R**	36.0	14.0	5.0	Ringless	**2540.00**	3
150	MBK150	20	40	**MC2040B1150RJBC**	—	36.0	14.0	5.0	Ringless	**2522.00**	3, 5
200	—	12	6	**MC0606L1200R**	**MC0606ML1200R**	27.0	14.0	5.0	Ringless	**1188.00**	1, 2, 3
200	—	12	6	**MC0606L1200RJB**	**MC0606ML12RB**	27.0	14.0	5.0	Ringless	**1216.00**	1, 2, 3, 5
200	—	12	6	**MC0606L1200RA**	—	27.0	14.0	5.0	Ringless	**1250.00**	1, 2, 3, 4
200	MBK200	4	8	**MC0408B1200T**	**MC0408MB1200T**	30.0	14.0	5.0	Ring	**1318.00**	3
200	MBK200	4	8	**MC0408B1200RT**	**MC0408MB1200RT**	30.0	14.0	5.0	Ringless	**1318.00**	3
200	MBK200	8	16	**MC0816B1200CT**	—	32.0	14.0	5.0	Ring	**1387.00**	3
200	MBK200	8	16	**MC0816B1200RCT**	—	32.0	14.0	5.0	Ringless	**1387.00**	3
200	MBK200	20	40	**MC2040B1200RC**	**MC2040MB1200R**	36.0	14.0	5.0	Ringless	**2540.00**	3
200	MBK200	20	40	**MC2040B1200RJBC**	—	36.0	14.0	5.0	Ringless	**2522.00**	3

Notes:
1. No main breaker provided. Accept QN or QP type 2 or 4-pole breakers.
2. Suitable for use as service entrance equipment when not more than six disconnecting means are provided and when not used as a lighting an appliance panel board.
3. Due to wire space restrictions on the trough side, the left side of the interior is limited to a 60A max branch.
4. Aluminum enclosure.
5. Horn bypass and 5th jaw included.

Meter Centers

Surface Mount Meter Load Centers, 1-Phase, 3-Wire 120/240V AC 100-200A *Selection*

- UL listed
- 22,000 AIC Rated
- Pad locking provisions on all devices
- Side hinge doors removable by backing out only one screw
- Suitable for use only as service entrance equipment
- Contact local utility to confirm meter socket approval prior to installation
- See end of section for dimensions and wiring diagrams

MC0816B1XXXH



200A OH/UG feed, 8 circuit, with feed thru lugs.

MC0816B1XXXT



200A Trailer Panel, OH feed only, 8 circuits with feed thru lugs.

MC2040B1150(R)/ MC2040B1200(R)/ MC1224B1125



200A, 20 Circuit, Side by Side Meter Combo

MC0816B1400RLTM/ MC0816B1350RLTM



One factory installed main, provisions for up to 200A field installed main, 8 circuits.

Overhead / Underground: 1-Phase, 3-Wire SN (22,000A IR)

Meter Load Center Combinations				UL: Overhead / Underground	EUSERC: Overhead / Underground	Catalog Number	Hub Provision	5th Jaw	Dimensions (inches)			Cover Type	List Price $	Foot Notes
Ampere Rating	Main Breaker	No. of Spaces	No. of Circuits						Height	Width	Depth			
125	Q2125H	12	24	OH/UG	—	**MC1224B1125**	RX	EMC5J	16.00	22.89	5.00	Ring	**1620.00**	2
125	EQ9675R	12	24	OH/UG	—	**MC1224MB1125R**	HS	EC5J	34.00	14.12	5.00	Ringless	**1620.00**	2
150	QN2150RH	8	16	OH	—	**MC0816B1150T**	RX	—	29.00	12.00	5.12	Ring	**1387.00**	1, 3
150	QN2150RH	8	16	OH/UG	—	**MC0816B1150TH**	2-RX	EMC5J	21.00	22.89	5.00	Ring	**1360.00**	1, 3
150	QN2150RH	8	16	OH/UG	—	**MC0816B1150RTH**	2-RX	EMC5J	21.00	22.89	5.00	Ringless	**1360.00**	1, 3
150	QN2150RH	20	40	OH/UG	—	**MC2040B1150**	RX	EMC5J	18.00	22.89	5.00	Ring	**2585.00**	2
150	QN2150RH	20	40	OH/UG	—	**MC2040B1150R**	RX	EMC5J	18.00	22.89	5.00	Ringless	**2522.00**	2
200	QN2200RH	8	16	OH	—	**MC0816B1200T**	RX	—	29.00	12.00	5.12	Ring	**1387.00**	1, 3
200	QN2200RH	8	16	OH	—	**MC0816B1200RT**	RX	—	29.00	12.00	5.12	Ringless	**1387.00**	1, 3
200	QN2200RH	8	16	OH/UG	—	**MC0816B1200TH**	2-RX	EMC5J	21.00	22.89	5.00	Ring	**1360.00**	1, 2
200	QN2200RH	8	16	OH/UG	—	**MC0816B1200RTH**	2-RX	EMC5J	21.00	22.89	5.00	Ringless	**1360.00**	1, 2
200	QN2200RH	20	40	OH/UG	—	**MC2040B1200**	RX	EMC5J	18.00	22.89	5.00	Ring	**2585.00**	2
200	QN2200RH	20	40	OH/UG	—	**MC2040B1200R**	RX	EMC5J	18.00	22.89	5.00	Ringless	**2522.00**	2
350	QN2150H	8	16	OH/UG	—	**MC0816B1350RLTM**	HD	—	29.00	27.00	6.00	Ringless	**3940.00**	1
400 NEW	QN2200H	4	8	OH/UG	—	**MC0408B1400RLTM**	HD	—	29.00	27.00	6.00	Ringless	**3591.00**	1
400	QN2200H	8	16	OH/UG	—	**MC0816B1400RLTM**	HD	—	29.00	27.00	6.00	Ringless	**3940.00**	1

① Feed thru lugs included.
② Side by side design for OH/UG applications.
③ Over/under design for OH applications.