SIEMENS

Data sheet 3VL2506-2PE30-0AA0



circuit breaker VL150 UL type DG (cat no. HDK3T060) non-interchangeable frame, with circuit breaker approval acc. to UL 489 high breaking capacity 3-pole; NEMA rating 65KA@480V and 18KA@600/347V (molded case circuit breaker) Electronic Trip Unit ETU, LSI TA=40°C In=60A, rated current ISD=1.5-10xIR, II=11xIN short-circuit protection Ir=30-60A Electronic Trip Unit for line protection without connection accessories without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	2.36 kg
Net Weight	2.36 kg

General Product Approval					Test Certificates
CSA	CCC	EG-Konf.	UKCA	EAC	Special Test Certificate

other			Dangerous goods	Environment	
Confirmation	Miscellaneous	Miscellaneous	Transport Information	Environmental Confirmations	Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2506-2PE30-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL2506-2PE30-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2506-2PE30-0AA0
CAx-Online-Generator
http://www.siemens.com/cax
Information- and Downloadcenter (catalogues, leaflets,...)
http://www.siemens.com/energy-automation





last modified: 4/8/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens