SIEMENS

NPX3B160

Documents

Others 1

Cut Sheets 2

Accessories

Product component / Auxiliary switch	0

Certificates

Certificate of suitability	UL

Connections

Type of electrical connection / for main current circuit	NO LUGS

Electricity

Continuous current / rated value	1600 A

General Technical Data

Operating voltage / rated value / maximum	600 V

Mechanical Design

Width	9 in
Depth	6.2 in
Height	16 in
Size of the circuit-breaker	PG - 1600A

Model

Product designation	MOLDED CASE CIRCUIT BREAKER
Design of the product	SYSTEM PROTECTION
Product brand name	SIEMENS
Protective function of the overcurrent release	LI
Number of poles	3
Design of the overcurrent release	MODEL 525

Switching Capacity

Maximum short-circuit current breaking capacity (Icu) / at 415 V / rated value	50 kA

Maximum short-circuit current breaking capacity (Icu) / at 240 V / rated value	65 kA
Maximum short-circuit current breaking capacity (Icu) / at 690 V / rated value	20 kA

Switching Capacity According To UI 489

Maximum short-circuit current breaking capacity (Icu) / at 480 V / acc. to NEMA / rated value	35 kA
Maximum short-circuit current breaking capacity (Icu) / at 600 V / acc. to NEMA / rated value	25 kA
Trip class	NORMAL
Maximum short-circuit current breaking capacity (Icu) / at 240 V / acc. to NEMA / rated value	65 kA

Information and Instruction 3

Delivery Information

Export Control Class	AL : N / ECCN : EAR99
Net Weight	54.95

Additional Product Information

EAN/UPC	70783643500111
Country of Origin	, MX, US
Commodity Code	8536200020
RoHS Compliance	*DQ

Information and Instruction 4

Speed Fax Sections 5



Speed Fax Sections 6