SIEMENS

Data sheet 6ES7231-4HF50-0XB0

SIMATIC S7-1200 G2: SM 1231 analog input, 8 AI; inputs: 8x AI 14 bit ADC (+/-10 V, +/-5 V, +/-2.5 V or 0-20 mA/4-20 mA)

Siemens EcoTech



Figure similar

General information	
Product type designation	SM 1231, AI 8x 14 bit
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	45 mA
from backplane bus 5 V DC, typ.	75 mA
Power loss	
Power loss, typ.	2.5 W
Analog inputs	
Number of analog inputs	8; Current or voltage differential inputs
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	1.25 ms; at 400 Hz rejection
Input ranges	
● Voltage	Yes; ±10V, ±5V, ±2.5V
● Current	Yes; 4 to 20 mA, 0 to 20 mA
● Thermocouple	No
● Resistance thermometer	No
● Resistance	No
Input ranges (rated values), voltages	
● -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	≥1 MOhm
● -2.5 V to +2.5 V	Yes
— Input resistance (-2.5 V to +2.5 V)	≥1 MOhm
● -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	≥1 MOhm
Input ranges (rated values), currents	
● 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	< 290 Ω, > 270 Ω
● 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	< 290 Ω, > 270 Ω

Subject to change without notice
© Copyright Siemens

Cable length	
● shielded, max.	100 m; shielded, twisted pair
Analog value generation for the inputs	
Measurement principle	successive approximation
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	13 bit; + sign
● Integration time, parameterizable	Yes
● Interference voltage suppression for interference frequency f1 in Hz	40 dB, DC to 60 Hz
Smoothing of measured values	
● parameterizable	Yes
● Step: None	Yes
● Step: low	Yes
● Step: Medium	Yes
● Step: High	Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C ±0.1 % / -20 °C to 60 °C ±0.2 % of the full-scale deflection
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.1 %
● Current, relative to input range, (+/-)	0.1 %
Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency	
● Common mode voltage, max.	12 V
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire-break	Yes
Diagnostics indication LED	
● DIAG LED	Yes
● for status of the inputs	Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
CSA approval	No
UL approval	Yes
cULus	Yes
FM approval	No
RCM (formerly C-TICK)	Yes
KC approval	No
Marine approval	No
Ecological footprint	
● environmental product declaration	Yes; type 2 acc. to ISO 14021
Global warming potential	
— global warming potential, (total) [CO2 eq]	32.2 kg
— global warming potential, (during production) [CO2 eq]	8 kg
— global warming potential, (during operation) [CO2 eq]	24.5 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.36 kg
Ambient conditions	
Free fall	
● Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
● min.	-20 °C
● max.	40 °C; at max. voltages and max. specifications
● horizontal installation, min.	-20 °C
● horizontal installation, max.	60 °C; at rated voltages, 50 % of max. specification and alternate IO active

Subject to change without notice
© Copyright Siemens

● vertical installation, min.	-20 °C
● vertical installation, max.	50 °C; at rated voltages, 50 % of max. specification and alternate IO active
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Operation, min.	540 hPa
● Operation, max.	1 140 hPa
● Storage/transport, min.	540 hPa
● Storage/transport, max.	1 140 hPa
Altitude during operation relating to sea level	
● Installation altitude, min.	-1 000 m
● Installation altitude, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Vibrations	
● Vibration resistance during operation acc. to IEC 60068-2-6	3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz
● Operation, tested according to IEC 60068-2-6	Yes
Shock testing	
● tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
Pollutant concentrations	
● SO2 at RH < 60% without condensation	S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
connection method	
required front connector	No
Mechanics/material	
Enclosure material (front)	
● Plastic	Yes
Dimensions	
Width	30 mm
Height	125 mm
Depth	100 mm
Weights	
Weight, approx.	175 g

Classifications

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420

Approvals / Certificates

General Product Approval				EMV
Manufacturer Declaration	CE EG-Konf.	UKCA	KC	KC

For use in hazardous locations	Environment

Subject to change without notice
© Copyright Siemens







CCC-Ex



last modified: 3/23/2025

Subject to change without notice
© Copyright Siemens