SIEMENS

## Data sheet 6ES7193-6AS00-0AA0



SIMATIC ET 200SP, BusAdapter BA-SEND BA1XFC, 1x FastConnect connection for ET connection

| | |
|---|---|
| **General information** | |
| Product type designation | BA-Send 1xFC |
| HW functional status | From FS05 |
| **Interfaces** | |
| Supports protocol for PROFINET IO | |
| Cable length | |
| — Cu conductors | 15 m; from IM firmware V3.3: between BA-send and the first ET-CONNECTION bus node and between all other bus nodes |
| ET-Connection | |
| ● Number of interfaces ET connection | 1 |
| ● FC (FastConnect) | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● horizontal installation, min. | -30 °C |
| ● horizontal installation, max. | 60 °C |
| ● vertical installation, min. | -30 °C |
| ● vertical installation, max. | 50 °C |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual |
| **Dimensions** | |
| Width | 20 mm |
| Height | 69.5 mm |
| Depth | 59 mm |
| **Weights** | |
| Weight, approx. | 44 g |

**last modified:** 9/22/2023


Subject to change without notice
© Copyright Siemens