SIEMENS

Data sheet 6ES7653-2CC00-0XB0

	SIMATIC System Expansion Card up to 500 process objects suitable for CPU 410-5H
General information	
Product type designation	PCS 7 System Expansion Card PO 500
HW functional status	3
Firmware version	V2.0
Design of PLC basic unit	With Conformal Coating (ISA-S71.04 severity level G1; G2; G3) and operating temperature to 70 °C
Memory	
PCS 7 process objects	500; PO for CPU 410-5H; expandable by means of CPU 410 Expansion Pack PO 100 or PO 500
Work memory	
● integrated	Use of max. 10 MB work memory in the CPU 410-5H
● expandable	Yes, by means of CPU 410 Expansion Pack PO 100 or PO 500
CPU-blocks	
DB	
● Size, max.	64 kbyte; the total size of all data blocks generated with the SFC 22 (CREATE_DB) is limited to 256 KB
Address area	
I/O address area	
● Inputs	Use of 16 KB in the CPU 410-5H
● Outputs	Use of 16 KB in the CPU 410-5H
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
CCC	Yes
Use in hazardous areas	
● ATEX	ATEX II 3G Ex ec IIC T4 Gc
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	70 °C
Ambient temperature during storage/transportation	
● min.	-25 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see section "Climatic and mechanical environmental conditions"
Resistance	
Usage in industrial process technology	
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes
Dimensions	
Width	8 mm
Height	16 mm
Depth	25 mm
Weights	

Subject to change without notice
© Copyright Siemens

Weight, approx.	20 g

last modified: 6/7/2024

Subject to change without notice
© Copyright Siemens