SIEMENS

Data sheet 6ES7132-7RD11-0AB0



SIMATIC DP, electronic module for ET200iSP, 4 DQ, 17.4 V DC/27 mA "H"-shutdown, Ex ib (ia Ga) IIC T4 Gb, Ex ib [ia IIIC Da] IIC T4 Gb, Ex ib [ia] I Mb

General information	
Product type designation	4DQ 17.4 V DC/27 mA
Input current	
Current consumption, typ.	260 mA
from load voltage L+ (without load), max.	300 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	2.1 W
Address area	
Address space per module	
● Address space per module, max.	2 byte
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	4; additionally 1 intrinsically-safe input for H shutdown
Short-circuit protection	Yes
No-load voltage Uao (DC)	17.4 V
Internal resistor Ri	150 Ω
Trend key points E	
● Voltage Ue (DC)	13.3 V
● Current Ie	27 mA
Output current	
● for signal "1" rated value	0.027 A
Output delay with resistive load	
● "0" to "1", max.	2 ms
● "1" to "0", max.	1.5 ms
Parallel switching of two outputs	
● for uprating	Yes
Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load, max.	2 Hz
Cable length	
● shielded, max.	500 m
● unshielded, max.	500 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes; Parameterizable
Diagnoses	
● Diagnostic information readable	Yes
● Wire-break	Yes

Subject to change without notice
© Copyright Siemens

● Short-circuit	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
● Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
● between the channels	No
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	Yes
Dimensions	
Width	30 mm
Height	129 mm
Depth	136.5 mm
Weights	
Weight, approx.	255 g

last modified: 8/30/2023

Subject to change without notice
© Copyright Siemens