SIEMENS

Data sheet 6GK5721-1FC00-0AB0



IWLAN client, SCALANCE W721-1, RJ45, 1 radio, 1 R-SMA antenna port, IEEE 802.11a/b/g/h/n, 2.4/5 GHz, gross data rate 150 Mbit/s, 1x RJ45 max. 100 Mbit/s, 24 V DC, terminal block, IP20, 0... +55°C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, scope of delivery: Manuals on CD-ROM, German/English, 1x terminal block; only for operation in USA

transfer rate	
transfer rate	
• with WLAN / maximum	150 Mbit/s
• for Industrial Ethernet	10, 100 Mbit/s
transfer rate / for Industrial Ethernet	
• minimum	10 Mbit/s
• maximum	100 Mbit/s

interfaces	
number of electrical connections	
• for network components or terminal equipment	1
• for power supply	1
• for redundant voltage supply	0
type of electrical connection	
• for network components or terminal equipment	RJ45 socket
• for power supply	3-pole screw terminal
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No

Subject to change without notice
© Copyright Siemens

interfaces / wireless	
number of radio cards / permanently installed	1
number of electrical connections / for external antenna(s)	1
type of electrical connection / for external antenna(s)	R-SMA (socket)
product feature / external antenna can be mounted directly on device	Yes

supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1	
• from terminal block	19.2 V
supply voltage / 2	
• from terminal block	28.8 V
consumed current	
• at DC / at 24 V / typical	0.15 A
power loss [W]	
• at DC / at 24 V / typical	3.6 W

ambient conditions	
ambient temperature	
• during operation	0 ... 55 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
protection class IP	IP20

design, dimensions and weights	
width	50 mm
height	114 mm
depth	74 mm
width / of the enclosure / without antenna	50 mm
height / of the enclosure / without antenna	114 mm
depth / of the enclosure / without antenna	74 mm
net weight	0.13 kg
fastening method	
• S7-300 rail mounting	No
• S7-1500 rail mounting	No
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	No

Subject to change without notice
© Copyright Siemens

radio frequencies	
• operating frequency / for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz; depending on the country approvals
• operating frequency / for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz; depending on the country approvals

product features, product functions, product components / general	
product function / Access Point Mode	No
product function / client Mode	Yes
product function	
• iPCF client	No
• iPCF-MC client	No
product function / iREF	No
product function / iPRP	No

product functions / management, configuration, engineering	
number of manageable IP addresses / in client	4
product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• configuration with STEP 7	Yes
• configuration with STEP 7 in the TIA Portal	Yes
• WDS	No
protocol / is supported	
• Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	No
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes

product functions / diagnostics	
product function	
• PROFINET IO diagnosis	No
• link check	No
• connection monitoring IP-Alive	No

Subject to change without notice
© Copyright Siemens

• SysLog	Yes
protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
product functions / VLAN	
product function	
• function VLAN with IWLAN	No
product functions / DHCP	
product function	
• DHCP client	Yes
• DHCP server	Yes
• DHCP Option 82	Yes
product functions / redundancy	
protocol / is supported	
• STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes
product functions / security	
product function	
• ACL - MAC-based	Yes
• management security, ACL-IP based	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	No
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
protocol / is supported	
• SSH	Yes
• RADIUS	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
• SIMATIC time synchronization (SIMATIC Time)	Yes
standards, specifications, approvals	
standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4

Subject to change without notice
© Copyright Siemens

• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
certificate of suitability	
• EC Declaration of Conformity	Yes
• CE marking	Yes
• C-Tick	Yes
• E1 approval	No
• railway application in accordance with EN 50155	No
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	No
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	No
• Power-over-Ethernet according to IEEE802.3at for type 2	No
• standard for wireless communication / IEEE 802.11a	Yes
• standard for wireless communication / IEEE 802.11b	Yes
• standard for wireless communication / IEEE 802.11e	Yes
• standard for wireless communication / IEEE 802.11g	Yes
• standard for wireless communication / IEEE 802.11h	Yes
• standard for wireless communication / IEEE 802.11i	Yes
• standard for wireless communication / IEEE 802.11n	Yes
wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• French marine classification society (BV)	No
• DNV GL	No
• Korean Register of Shipping (KRS)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No
• Royal Institution of Naval Architects (RINA)	No

© Copyright Siemens

accessories	
accessories	24 V DC screw terminal included in scope of delivery

further information / internet-Links	
Internet-Link	
• to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to the website: IWLAN	http://www.siemens.com/iwlan
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	11/03/2020

© Copyright Siemens