SIEMENS

Show actual product details

Data sheet 6GK1905-0AB10

Product type designation

SpliT Connect M12 Outlet
PROFIBUS PA SPLITCONNECT M12 OUTLET, INSERT ELEMENT F. DIRECT CONN. FROM PROFIBUS PA FIELD DEVICES TO SPLITCONNECT TAP USING M12 INTERFACE (TURNABLE OUTLET) PACK.: 5 PCS = 1 PACK



Electrical data	
Transfer rate / with PROFIBUS PA	31.25 kbit/s
Permitted ambient conditions	
Ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Protection class IP	IP67
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax

Subject to change without notice
© Copyright Siemens AG

- to website: Industry Online Support https://support.industry.siemens.com

last modified: 07/08/2016

Subject to change without notice
© Copyright Siemens AG