SIEMENS

Show actual product details

Data sheet 6GK5788-2GD00-1AA0

Product type designation

SCALANCE W788C-2 M12

IWLAN ACCESS POINT, SCALANCE W788C-2 M12, FOR USE WITH IWLAN-CONTROLLER, 2 RADIOS, 6 N-CON. ANT.CONNECT. IEEE 802.11A/B/G/H/N, 2.4/5GHZ, BRUTTO 450 MBIT/S PRO RADIO, 1 X M12 (MAX. 1 GBIT/S), POE, 24VDC, IP65 (-20-+60 GRD C), POE, WPA2/802.11I/E, NOTE NAT. APPROVALS CONTROLLER! (CERT ID: RAPN-W2-M12-E3) Contains MPCIE-R1-ABGN-U3 SCOPE OF SUPPLY:MANUALS ON CD, GERMAN/ENGLISH.



Transmission rate	
Transfer rate	
• with WLAN / maximum	450 Mbit/s
• for Industrial Ethernet	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10 Mbit/s, 1000 Mbit/s
Interfaces	
Number of electrical connections	
• for network components or terminal equipment	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for network components or terminal equipment	M12 interface (8-pole, X-coded), PoE
• for power supply	M12 interface (4-pole, A-coded)
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No
Interfaces / wireless	
Number of radio cards / permanently installed	2

Subject to change without notice
© Copyright Siemens AG

Transmission mode / for multiple input multiple output (MIMO)	3x3
Number of spatial streams	3
Number of electrical connections / for external antenna(s)	6
Type of electrical connection / for external antenna(s)	N-Connect (socket)
Product feature / external antenna can be mounted directly on device	Yes

Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1	
• from M12 Power Connector (A-coded) for redundant power supply	19.2 V
Supply voltage / 2	
• from M12 Power Connector (A-coded) for redundant power supply	28.8 V
Supply voltage	
• from Power-over-Ethernet acc. to IEEE802.3at for type 1 and IEEE802.3af	48 V
• from Power-over-Ethernet acc. to IEEE802.3at for type 2	50 V
Consumed current	
• at DC / at 24 V / typical	0.63 A
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	0.22 A
• with Power-over-Ethernet according to IEEE802.3at for type 2 / typical	0.3 A
Power loss [W]	
• at DC / at 24 V / typical	15 W
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	10.7 W
• with Power-over-Ethernet according to IEEE802.3at for type 2 / typical	15 W

Permitted ambient conditions	
Ambient temperature	
• during operation	-20 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	90 %
Ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W788-x or W748-x product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.

© Copyright Siemens AG

Protection class IP	IP65
Design, dimensions and weight	
Width / of the enclosure / without antenna	200 mm
Height / of the enclosure / without antenna	176 mm
Depth / of the enclosure / without antenna	79 mm
Net weight	1.7 kg
Mounting type	For mounting on 35 mm DIN rail, an additional mounitng adapter is required
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	Yes
• wall mounting	Yes
Wireless frequencies	
Operating frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz
• for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz
Product properties, functions, components / general	
Product function / Access Point Mode	Yes
Product function / Client Mode	No
Number of SSIDs	16
Product functions / management, configuration	
Product function	
• operation with IWLAN controller	Yes
• operation with Enterasys WLAN controller	Yes
Product functions / DHCP	
Product function	
• DHCP client	Yes
Product functions / Time	
Protocol / is supported	
• SIMATIC Time	No
Standards, specifications, approvals	
Standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
Certificate of suitability	
• EC declaration of conformity	Yes

© Copyright Siemens AG

• CE marking	Yes
• C-Tick	Yes
• CCC	No
• E1 approval	Yes
• Railway application in accordance with EN 50155	Yes
• Fire protection in accordance with EN 45545-2	Yes
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	No
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	Yes
• Power-over-Ethernet according to IEEE802.3at for type 2	Yes
Standard for wireless communication	
• IEEE 802.11a	Yes
• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes
• IEEE 802.11n	Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No

Further Information / Internet Links

Internet-Link	
• to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to the website: IWLAN	http://www.siemens.com/iwlan
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax

© Copyright Siemens AG

• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	07/20/2016

Subject to change without notice
© Copyright Siemens AG