SIEMENS

## Data sheet 5SM2325-0

RC unit for 5SY, 2-pole, type AC, In: 63 A, 30 mA, Un AC: 230 V



| Model | |
|---|---|
| Product brand name | SENTRON |
| Product designation | RC unit |
| Design of the product | Instantaneous |
| Product variations | for 5SY |

| General technical data | |
|---|---|
| Number of poles | 2 |
| Size of installation devices / acc. to DIN 43880 | 1 |
| Protection against electrical shock | Finger and back-of-hand safe |
| circuit-breaker / Design | 5SM2 |
| Mechanical service life (switching cycles) / typical | 10 000 |
| Switching function / short-term delayed | No |
| Overvoltage category | III |
| Insulation voltage / rated value | 460 V |

| Supply voltage | |
|---|---|
| Operating current / at AC / rated value | 63 A |
| Supply voltage | |
| • at AC / rated value | 230 V |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| • for testing equipment / minimum | 195 V |
| Operating frequency | 50 Hz |
| Supply voltage frequency | |
| • rated value | 50 Hz |

## Protection class

| | |
|---|---|
| Protection class IP | IP20, if the distribution board is installed, with connected conductors |

## Dissipation

| | |
|---|---|
| Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 4.6 W |

## Current

| | |
|---|---|
| Tripping residual current / rated value | 30 mA |
| Tripping residual / rated value / derated current | |
| • at 40 Cel | 58.59 A |
| • at 45 Cel | 58.59 A |
| • at 50 Cel | 56.7 A |
| • at 55 Cel | 54.81 A |
| • at 60 Cel | 53.55 A |
| • at 65 Cel | 52.29 A |
| • at 70 Cel | 50.4 A |
| Type of fault current | AC |

## Product details

| | |
|---|---|
| Product feature / silicon-free | Yes |
| Product extension / can be installed / supplementary devices | Yes |

## Connections

| | |
|---|---|
| Connectable conductor cross-section / solid | |
| • minimum | 1.5 mm² |
| • maximum | 25 mm² |
| Connectable conductor cross-section / stranded | |
| • minimum | 1.5 mm² |
| • maximum | 25 mm² |
| Tightening torque / with screw-type terminals | |
| • minimum | 2.5 N·m |
| • maximum | 3 N·m |
| Position / of power supply cord | top or bottom |

## Mechanical Design

| | |
|---|---|
| Height | 90 mm |
| Width | 71 mm |
| Depth | 70 mm |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| Installation depth | 70 mm |
| Number of width units | 2 |
| Mounting type | DIN rail (REG) |
| Mounting position | any |
| Net weight | 209 g |

## Environmental conditions

| | |
|---|---|
| Ambient temperature | |
| • minimum | -5 °C |
| • maximum | 45 °C |
| Ambient temperature / during storage | |
| • minimum permissible | -40 °C |
| • maximum permissible | 75 °C |

## Certificates

| | |
|---|---|
| Reference code | |
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

| General Product Approval | Declaration of Conformity | Test Certific-ates | other |
|---|---|---|---|
| Miscellaneous | | Miscellaneous | Miscellaneous |
| CCC | EG-Konf. | | |

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,…)**
http://www.siemens.com/lowvoltage/catalogs

**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SM2325-0


**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/5SM2325-0

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2325-0

**CAx-Online-Generator**
http://www.siemens.com/cax

**Tender specifications**
http://www.siemens.com/specifications


Subject to change without notice
© Copyright Siemens





Subject to change without notice
© Copyright Siemens