SIEMENS

## Data sheet 6AV2181-5AR80-0AX0

Spare key type 13 for key-operated switch KTP Mobile Panels 2nd Generation
Further information, Quantity and content: see technical data



Figure similar

| | |
|---|---|
| **General information** | |
| Product type designation | Spare key |
| **Standards, approvals, certificates** | |
| CE mark | No; No CE marking obligation |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | -40 °C |
| ● max. | 80 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -40 °C |
| ● max. | 80 °C |
| Relative humidity | |
| ● Operation, max. | 90 % |
| **Mechanics/material** | |
| Material | |
| ● Sheet steel | Yes; Handle made of plastic |
| **Dimensions** | |
| Width | 15 mm |
| Height | 35 mm |
| Thickness | 4 mm |
| **Weights** | |
| Weight (without packaging) | 5 g |
| **Scope of supply** | |
| Delivery quantity in pieces | 5 |
| **Other** | |
| Merchandise | No |
| Manufacturer name | SIEMENS AG |
| Manufacturer's address | Gleiwitzerstraße 555, 90475 Nuremberg, Germany |
| Target devices | For Mobile Panel 2nd Generation |
| Usable in the following products | |
| ● Product 1 | 6AV2125-2* |
| ● Product 2 | 6AV2145-* |

**last modified:** 8/11/2023


Subject to change without notice
© Copyright Siemens