SIEMENS

## Data sheet US2:WP4212



Siemens Low Voltage's Multi-Family Metering Line of PAK Metering: Standard 225A as part of the PAK Metering: Standard 225A Group. Type: UNI-PAK Features: NO BYPASS Appn: GARDEN - STYLE Std: UL-50,67,414 V. Rating: 120/240V A. Rating: 400 A phase: 1PH size: 9.00 x 28.79 x 30.630 No. Of Cutouts: 11 Cutout Size: 1 x (1/2,3/4,1,1-1/4"), 6 x (2-1/2,2,1-1/2,1-1/4,1"), 2 x (4,3-1/2,3,2-1/2,2"), 2X4" Cable Entry: TOP OR BOTTOM FEED Terminal: 3X2 STUDS. Insulated.Appn:. Wall Mounted. Enclosure: RING

| | |
|---|---|
| Cable entry type | TOP OR BOTTOM FEED |
| Mounting type | WALL MOUNTED |
| Suitability for operation | GARDEN-STYLE |

### Electricity

| | |
|---|---|
| Ampacity | 400 A |

### Model

| | |
|---|---|
| Product brand name | Siemens |
| Product type designation | UNI-PAK |
| Special product feature | NO BYPASS |

### Mechanical Design

| | |
|---|---|
| Design of the terminal strip | 3X2 STUDS |

### General product approval

| | |
|---|---|
| Certificate of suitability | UL-50;67;414 |

**last modified:** 10/29/2019


Subject to change without notice
© Copyright Siemens