SIEMENS

Show actual product details

Data sheet 6GK5786-2FC00-1AA0

Product type designation



SCALANCE W786C-2 RJ45

IWLAN ACCESS POINT, SCALANCE W786C-2 RJ45, FOR USE WITH IWLAN-CONTROLLER, 2 RADIOS, 6 R-SMA ANT.CONNECT., IEEE 802.11A/B/G/H/N, 2.4/5GHZ, BRUTTO 450 MBIT/S PRO RADIO, 1 X RJ45 (MAX. 1 GBIT/S), POE, 24VDC, IP65 (-40-+60 DGR C), POE, WPA2/802.11I/E, NOTE NAT. APPROVALS CONTROLLER! (CERT ID: EAPN-W2-RJ-E3) Contains MPCIE-R1-ABGN-U3 SCOPE OF SUPPLY:MANUALS ON CD, GERMAN/ENGLISH, 1 X TERMINAL BLOCK.

Transmission rate	
Transfer rate	
• with WLAN / maximum	450 Mbit/s
• for Industrial Ethernet	10 Mbit/s, 1000 Mbit/s, 1000 Mbit/s, 10 Mbit/s, 1000 Mbit/s

Interfaces	
Number of electrical connections	
• for network components or terminal equipment	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for network components or terminal equipment	RJ45 socket
• for power supply	2-pole connector (24 V DC) or optionally available power supply adapter (4-pole 24 V DC or 3-pole 110 to 230 V AC)
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No

Interfaces / wireless

Subject to change without notice
© Copyright Siemens AG

Number of radio cards / permanently installed	2
Transmission mode / for multiple input multiple output (MIMO)	3x3
Number of spatial streams	3
Number of electrical connections / for external antenna(s)	6
Type of electrical connection / for external antenna(s)	R-SMA (socket)
Product feature / external antenna can be mounted directly on device	No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / 1	
• from terminal block	19.2 V
Supply voltage / 2	
• from terminal block	28.8 V
Supply voltage	
• from Power-over-Ethernet acc. to IEEE802.3at for type 1 and IEEE802.3af	48 V
• from Power-over-Ethernet acc. to IEEE802.3at for type 2	50 V
• from optional integrable power supply	
— at AC	100 ... 240 V
— at DC	12 ... 24 V
Consumed current	
• at DC / at 24 V / typical	0.63 A
• at AC / at 230 V / typical	0.07 A
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	0.22 A
Power loss [W]	
• at DC / at 24 V / typical	15 W
• at AC / at 230 V / typical	15 W
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	10.7 W

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	100 %
Ambient condition / for operation	When using the power supply 100 to 240 V AC, an operating temperature of -40 °C to +60 °C is permissible
Protection class IP	IP65

Subject to change without notice
© Copyright Siemens AG

Design, dimensions and weight	
Width / of the enclosure / without antenna	251 mm
Height / of the enclosure / without antenna	251 mm
Depth / of the enclosure / without antenna	72 mm
Net weight	2.24 kg
Mounting type	For mast mounting, 35 mm DIN rail mounting and S7-300 rail mounting, an additional support plate is required
• S7-1500 rail mounting	No
• wall mounting	Yes

Wireless frequencies	
Operating frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz
• for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz

Product properties, functions, components / general	
Product function / Access Point Mode	Yes
Product function / Client Mode	No
Number of SSIDs	16
Product function	
• Dual Client	No

Product functions / management, configuration	
Product function	
• operation with IWLAN controller	Yes
• operation with Enterasys WLAN controller	Yes

Product functions / DHCP	
Product function	
• DHCP client	Yes

Product functions / Time	
Protocol / is supported	
• SIMATIC Time	No

Standards, specifications, approvals	
Standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
Certificate of suitability	
• EC declaration of conformity	Yes
• CE marking	Yes

Subject to change without notice
© Copyright Siemens AG

• C-Tick	Yes
• CCC	No
• E1 approval	Yes
• Railway application in accordance with EN 50155	No
• Railway application in accordance with EN 50121-4	Yes
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	Yes
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	Yes
• Power-over-Ethernet according to IEEE802.3at for type 2	Yes
Standard for wireless communication	
• IEEE 802.11a	Yes
• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes
• IEEE 802.11n	Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No

Accessories

accessories	24 V DC screw terminal included in scope of delivery

Further Information / Internet Links

Internet-Link	
• to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to the website: IWLAN	http://www.siemens.com/iwlan
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter

Subject to change without notice
© Copyright Siemens AG

• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	07/08/2016

Subject to change without notice
© Copyright Siemens AG