Cross-Reference

General-Duty

Ampere Rating	Catalog Number Eaton	General Electric	Siemens	Square D
Plug Fuse, Single-Pole, Two-Wire, 120 Vac, NEMA 1				
30	**DP111NGB**	TPF130	LF111N	D211N
Plug Fuse, Two-Pole, Three-Wire, 240 Vac, NEMA 1				
30	**DP221NGB**	TPF230	LF211N	D211N
Fusible, Two-Pole, Three-Wire, 240 Vac, NEMA 1				
30	**DG221NGB**	TG3221	GF221N	D221N
60	**DG222NGB**	TG3222	GF222N	D222N
100	**DG223NGB**	TG3223	GF223N	D223N
200	**DG224NGK**	TG3224	GF224N	D224N
400	**DG225NGK**	TG3225	GF225N	D225N
600	**DG226NGK**	TG3226	GF226N	D226N
Fusible, Three-Pole, Three-Wire, 240 Vac, NEMA 1				
30	**DG321NGB**	TG4321	GF321N	D321N
60	**DG322NGB**	TG4322	GF322N	D322N
100	**DG323NGB**	TG4323	GF323N	D323N
200	**DG324NGK**	TG4324	GF324N	D324N
400	**DG325FGK**	TG3325	GF325N	D325N
600	**DG326FGK**	TG3326	GF326N	D326N
Fusible, Three-Pole, Four-Wire, 240 Vac, NEMA 1				
30	**DG321NGB**	TG4321	GF321N	D321N
60	**DG322NGB**	TG4322	GF322N	D322N
100	**DG323NGB**	TG4323	GF323N	D323N
200	**DG324NGK**	TG4324	GF324N	D324N
400	**DG325NGK**	TG4325	GF325N	D325N
600	**DG326NGK**	TG4326	GF326N	D326N
Non-Fusible, Two-Pole, Two-Wire, 240 Vac, NEMA 1				
30	**DG221UGB**	TGN3321	N/A	N/A
60	**DG222UGB**	TGN3322	N/A	QO260NATS
100	**DG223UGB**	TGN3323	N/A	QO2000NS
200	**DG324UGK**	TGN3324	N/A	DU324
400	**DG325UGK**	TGN3325	N/A	DU325
600	**DG326UGK**	TGN3326	N/A	DU326
Non-Fusible, Three-Pole, Three-Wire, 240 Vac, NEMA 1				
30	**DG321UGB**	TGN3321	GNF321	DU321
60	**DG322UGB**	TGN3322	GNF322	DU322
100	**DG323UGB**	TGN3323	GNF323	DU323
200	**DG324UGK**	TGN3324	GNF324	DU324
400	**DG325UGK**	TGN3325	GNF325	DU325
600	**DG326UGK**	TGN3326	GNF326	DU326

General-Duty, continued

Ampere Rating	Catalog Number Eaton	General Electric	Siemens	Square D
Fusible, Two-Pole, Three-Wire, 240 Vac, NEMA 3R				
30	**DG221NRB**	TG3221R	GF221NR	D221NRB
60	**DG222NRB**	TG3222R	GF222NR	D222NRB
100	**DG223NRB**	TG3223R	GF223NR	D223NRB
200	**DG224NRK**	TG3224R	GF224NR	D224NRB
400	**DG225NRK**	TG3225R	GF225NR	D225NR
600	**DG226NRK**	TG3226R	GF226NR	D226NR
Fusible, Three-Pole, Three-Wire, 240 Vac, NEMA 3R				
30	**DG321NRB**	TG4321R	GF321NR	D321NRB
60	**DG322NRB**	TG4322R	GF322NR	D322NRB
100	**DG323NRB**	TG4323R	GF323NR	D323NRB
200	**DG324NRK**	TG4324R	GF324NR	D324NRB
400	**DG325FRK**	TG3325R	GF325NR	D325NR
600	**DG326FRK**	TG3326R	GF326NR	D326NR
Fusible, Three-Pole, Four-Wire, 240 Vac, NEMA 3R				
30	**DG321NRB**	TG4321R	GF321NR	D321NRB
60	**DG322NRB**	TG4322R	GF322NR	D322NRB
100	**DG323NRB**	TG4323R	GF323NR	D323NRB
200	**DG324NRK**	TG4324R	GF324NR	D324NRB
400	**DG325NRK**	TG3325R ①	GF325NR	D325NR
600	**DG326NRK**	TG3326R ①	GF326NR	D326NR
Non-Fusible, Two-Pole, Two-Wire, 240 Vac, NEMA 3R				
30	**DG221URB**	TGN3321R	GNF321R	DU221RB
60	**DG222URB**	TGN3322R	GNF322R	DU222RB
100	**DG223URB**	TGN3323R	GNF323R	QO2000NRB
200	**DG324URK**	TGN3324R	GNF324R	DU324RB
Non-Fusible, Three-Pole, Three-Wire, 240 Vac, NEMA 3R				
30	**DG321URB**	TGN3321R	GNF321R	DU321RB
60	**DG322URB**	TGN3322R	GNF322R	DU322RB
100	**DG323URB**	TGN3323R	GNF323R	DU323RB
200	**DG324URK**	TGN3324R	GNF324R	DU324RB
400	**DG325URK**	N/A	N/A	N/A
600	**DG326URK**	N/A	N/A	N/A

Notes

① Separate neutral kit required.

Always verify the number of poles and wires required since catalog numbers may appear in multiple tables.

DG321NRB



120/240 Vac General-Duty, Fusible, Single-Throw, continued

System	Ampere Rating	Fuse Type Provision	Maximum Horsepower Ratings ① Single-Phase AC 120V	Single-Phase AC 240V	Three-Phase AC 240V	DC 250V	NEMA 1 Enclosure Indoor Catalog Number	NEMA 3R Enclosure Rainproof Catalog Number
Cartridge Type—Three-Pole, Three-Wire (Three Blades, Three Fuses)—240 Vac								
	30	—	—	—	—	—	②	②
	60	—	—	—	—	—	②	②
	100	—	—	—	—	—	②	②
	200	H	—	15	25–60	—	**DG324FGK** ③④	②
	400	H	—	—	50–125	—	**DG325FGK** ③④	**DG325FRK** ③④
	600	H	—	—	75–200	—	**DG326FGK** ③④	**DG326FRK** ③④
Cartridge Type—Four-Wire (Three Blades, Three Fuses, S/N)—120/240 Vac								
	30	H	—	1-1/2–3	3–7-1/2	—	**DG321NGB** ⑤	**DG321NRB** ⑤
	60	H	—	3–10	7-1/2–15	—	**DG322NGB** ⑤	**DG322NRB** ⑤
	100	H	—	7-1/2–15	15–30	—	**DG323NGB** ⑤	**DG323NRB** ⑤
	200	H	—	15	25–60	—	**DG324NGK**	**DG324NRK**
	400	H	—	—	50–125	—	**DG325NGK**	**DG325NRK**
	600	H	—	—	75–200	—	**DG326NGK**	**DG326NRK**

DG322URB



120/240 Vac General-Duty, Non-Fusible, Single-Throw

System	Ampere Rating	Maximum Horsepower Ratings Single-Phase AC 120V	Single-Phase AC 240V	Three-Phase AC 240V	DC 250V	NEMA 1 Enclosure Indoor Catalog Number	NEMA 3R Enclosure Rainproof Catalog Number
Two-Pole, Two-Wire (Two Blades)—240 Vac							
	30	2	3	—	—	**DG221UGB** ④⑤	**DG221URB** ④⑤
	60	3	10	—	—	**DG222UGB** ④⑤	**DG222URB** ④⑤
	100	—	15	—	—	**DG223UGB** ④⑤	**DG223URB** ④⑤
	200	—	15	—	—	④⑥	**DG224URK** ④
Three-Pole, Three-Wire (Three Blades)—240 Vac							
	30	2	3	7-1/2	—	**DG321UGB** ④⑤	**DG321URB** ④⑤
	60	3	10	15	—	**DG322UGB** ④⑤	**DG322URB** ④⑤
	100	—	15	30	—	**DG323UGB** ④⑤	**DG323URB** ④⑤
	200	—	15	60	—	**DG324UGK** ④	**DG324URK** ④
	400	—	—	125	—	**DG325UGK** ⑦	**DG325URK** ⑦
	600	—	—	200	—	**DG326UGK** ⑦	**DG326URK** ⑦

Notes

① Maximum hp ratings apply only when dual element time delay fuses are used.
② Use four-wire catalog numbers below.
③ Solid neutral bars are not included. Order separately from table on **Page V2-T1-14**.
④ **WARNING!** Switch is not approved for service entrance unless a neutral kit is installed.
⑤ These switches do not have an interlock that prevents door from being opened when switch is in the ON position.
⑥ Use three-wire catalog numbers below.
⑦ Drilled to accept field installed neutral kits.

All general-duty safety switches are individually packaged.

Accessories are limited in scope on general-duty safety switches. See **Page V2-T1-14** for availability. In addition, clear line shields are available as an accessory on 200–600A general-duty switches. Catalog Numbers: 200A = 70-7759-11, 400A = 70-8063-8, 600A = 70-8064-8.