SIEMENS

Data sheet 6GT2811-6CA10-2AA0

product type designation



Reader RF685R CMIIT

SIMATIC RF600 Reader RF685R CMIIT; Interfaces: Ethernet M12 PROFINET M12 1 integrated antenna+1 ext. antenna port, 4 dig. inputs/ 4 dig. outputs, 24 V DC; IP65; -25 to +55 °C; without accessories.

suitability for operation	RF600 Transponder, for direct connection to Ethernet, PROFINET, EtherNet/IP or PROFIBUS via communication module, OPC UA server integrated
radio frequencies	
operating frequency	920 ... 925 MHz
transmit power	3 ... 2000 mW
effective radiated power	
● for each external antenna / maximum	2000 mW
● minimum	10 mW
● maximum	2000 mW
range / maximum	8 m; Extended ranges possible, see RF600 System Manual, Range table: http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	EPCglobal Class 1 Gen 2 V2 / ISO/IEC 18000-62/-63
transfer rate / with radio transmission / maximum	400 kbit/s
product feature / multitag-capable	Yes
polarization	Linear (h/v), circular, combined
electrical data	
transmission time / for user data	
● for write access / per byte / typical	2 ms
● for read access / per byte / typical	0.15 ms
interfaces	
number of external antennas	1
standard for interfaces / for communication	Ethernet, PROFINET, OPC UA, EtherNet/IP, RS422
type of electrical connection	
● for external antenna(s)	RP-TNC
● for supply voltage	M12, 8-pin, connector
● for communications interface	2 x M12 4-pin D-coded, M12 8-pin (RS422)
● at the digital inputs/outputs	M12, 12-pin, female connector
number of digital inputs	4
number of digital outputs	4
mechanical data	
material	Aluminum, Pocan
color	silver, TI-Grey
mounting distance / relating to metal surfaces / recommended / minimum	0 mm
supply voltage, current consumption, power loss	
supply voltage	
● at DC / rated value	24 V
● at DC	20 ... 30 V
consumed current / at DC	
● at 24 V / typical	0.38 A

Subject to change without notice
© Copyright Siemens

● at 24 V / maximum	2 A
ambient conditions	
ambient temperature	
● during operation	-25 ... +55 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
ambient condition / for operation	With operating temperature below -20 °C: Warming-up time at least 10 minutes
protection class IP	IP65
shock resistance	EN 60068-2-27, EN 60068-2-6
shock acceleration	250 m/s²
vibrational acceleration	30 m/s²
resistance to mechanical stress	The maximum values for shock and vibration acceleration must not occur as continuous stress and they apply exclusively to assembly using screws
design, dimensions and weights	
width	258 mm
height	258 mm
depth	80 mm
net weight	2.47 kg
fastening method	Vesa 100 with 4 x M4 screws, top-hat rail 35 mm, profile rail S7-300, S7-1200 or S7-1500
wire length	
● of antenna cable / minimum	1 m
● of antenna cable / maximum	40 m
product features, product functions, product components / general	
display version	two LED rows with 8 and 9 LEDs
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function / of the PROFINET IO device / is supported / H-Sync forwarding	No
protocol / is supported	
● LLDP	Yes
● PROFINET IO protocol	Yes
● TCP/IP	Yes
● SNMP v1	Yes
● SNMP v2	No
● SNMP v3	No
● DCP	Yes
● EtherNet/IP protocol	Yes
● OPC UA	Yes
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	wireless acc. to CMIIT, OPC UA: embedded UA Server Profile
certificate of suitability	
● IECEx	No
MTBF	29 a
accessories	
accessories	one external antenna, set for mounting on top-hat rail or profile rail
further information / internet links	
internet link	
● to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
● to website: Industrial communication	http://www.siemens.com/ident/rfid
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

last modified: 8/11/2023

Subject to change without notice
© Copyright Siemens