SIEMENS

## Data sheet 6ES7193-6AP00-0AA0



SIMATIC ET 200SP, BusAdapter BA 2xSCRJ, 2 SCRJ FO connections

| | |
|---|---|
| **General information** | |
| Product type designation | BA 2xSCRJ |
| HW functional status | from FS04 |
| **Interfaces** | |
| Number of PROFINET interfaces | 1; 2 ports (switch) SCRJ FO |
| Supports protocol for PROFINET IO | |
| ● Number of SCRJ ports | 2 |
| Cable length | |
| — PCF | 100 m |
| — Plastic FOC (POF) | 50 m |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● horizontal installation, min. | -25 °C |
| ● horizontal installation, max. | 60 °C |
| ● vertical installation, min. | -25 °C |
| ● vertical installation, max. | 50 °C |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual |
| **Dimensions** | |
| Width | 20 mm |
| Height | 69.5 mm |
| Depth | 59 mm |
| **Weights** | |
| Weight, approx. | 50 g |

**last modified:** 8/16/2023


Subject to change without notice
© Copyright Siemens