SIEMENS

Data sheet 5SU1354-7LB13

RCBO, 10 kA, 1P+N, type A, short-time-delayed G, super-resistant K, 30 mA, C-Char, In: 13 A, Un AC: 230 V



Model	
Product brand name	SENTRON
Product designation	RCBO
Design of the product	Short-time delayed G, super resistant K

General technical data	
Number of poles	2
Number of poles / Note	1P+N
Number of poles / with protection	1
Tripping characteristic class	C
circuit-breaker / Design	5SU1
Mechanical service life (switching cycles) / typical	10 000
Overvoltage category	III
Degree of pollution	2

Voltage	
Surge current resistance / at (8/20) µs	3 kA

Supply voltage	
Type of voltage	AC
Operating current / at AC / rated value	13 A

Subject to change without notice
© Copyright Siemens

Supply voltage	
• at AC / rated value	230/240 V
• for testing equipment / minimum	195 V
Operating frequency	50/60 Hz
Supply voltage frequency / rated value	50 Hz

Protection class

Protection class IP	IP20, if the distribution board is installed, with connected conductors

Switching capacity

Breaking capacity short-circuit current (Icn) / according to EN 61009-1 / rated value	10 kA
Switching capacity current	
• acc. to EN 60898 / rated value	10 kA
• acc. to IEC 60947-2 / rated value	20 kA
Rated residual switching capacity (IΔm) / according to IEC 61009-1	10 kA
Energy limiting class	3

Dissipation

Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	2.2 W
• maximum	4.4 W

Current

Tripping residual current / rated value	30 mA
Tripping residual / rated value / derated current	
• at 30 Cel	13 A
• at 40 Cel	12.48 A
• at 45 Cel	12.22 A
• at 50 Cel	11.96 A
• at 55 Cel	11.57 A
• at 60 Cel	11.31 A
• at 65 Cel	10.53 A
• at 70 Cel	10.01 A
Type of fault current	A

Product details

Product function / neutral conductor switching	Yes
Product feature / Touch protection	Yes
Product feature	
• halogen-free	Yes
• silicon-free	Yes

Subject to change without notice
© Copyright Siemens

Connections	
Connectable conductor cross-section / solid	
• minimum	0.75 mm²
• maximum	35 mm²
Connectable conductor cross-section / stranded	
• minimum	0.75 mm²
• maximum	35 mm²
Connectable conductor cross-section / finely stranded / with core end processing	
• minimum	0.75 mm²
• maximum	25 mm²
Tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
Position / of power supply cord	Either top or bottom

Mechanical Design	
Height	90 mm
Width	36 mm
Depth	77 mm
Installation depth	70 mm
Number of width units	2
Mounting position	any
Net weight	294 g

Environmental conditions	
Influence of the surrounding temperature	Max. 95% humidity
Ambient temperature	
• minimum	-25 °C
• maximum	55 °C
Ambient temperature / during storage	
• minimum	-40 °C
• maximum	75 °C
Number of test cycles / for environmental testing / acc. to IEC 60068-2-30	28

Certificates	
Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

© Copyright Siemens

General Product Approval			Declaration of Conformity	Test Certific-ates	other
VDE	Miscellaneous	RCM	EG-Konf.	Special Test Certi-ficate	Miscellaneous

Railway
Vibration and Shock

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1354-7LB13

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SU1354-7LB13

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1354-7LB13

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
http://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens





Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens