SIEMENS

## Data sheet US2:HF364SS



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switch. 3-Pole 3-Wire Fused in a type 4/4X 316 grade Stainless Steel enclosure. Rated 600VAC (200A).

| | |
|---|---|
| **General technical data** | |
| mechanical service life (operating cycles) typical | 8000 |
| fastening method | SURFACE |
| number of poles | 3 |
| suitability for operation | DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS |
| **Electricity** | |
| ampacity | 200 A |
| supply voltage frequency rated value 50/60 Hz | Yes |
| **Environmental conditions** | |
| ambient temperature during operation maximum | 85 °C |
| ambient temperature during operation minimum | -29 °C |
| **Model** | |
| product brand name | SIEMENS |
| product sub brand name | VBII |
| product type designation | HEAVY DUTY SWITCH |
| type of electrical connection | MECHANICAL LUGS |
| **Mechanical Design** | |
| design of the housing | TYPE 4X |
| design of the actuating element | SINGLE THROW |
| material | 316 STAINLESS STEEL |
| **General product approval** | |
| certificate of suitability | UL98 / CUL |

**last modified:** 7/18/2024


Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens