SIEMENS

Data sheet US2:RH173GR



Siemens Low Voltage Talon Meter Sockets Commercial - Talon Meter Sockets HQU 7 200A Steel are Residential Enclosures Single-Family Metering. Type: HQU Features: W/ LEVER BYPASS Application: COMMERCIAL Std: UL V. Rating: 600V A. Rating: 200A Phase: 3 PHASE Size: 6.0 x 13.8 x 20.2 No Of Cutouts: 8 Cutout Size: 1 x 2.750, 3 x (1, 1-1/2, 2, 2-1/2, 3), 1 x 1/2, 3 x (3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3) Cable Entry: OH/UG Terminals: 7. Surface mounting. Operating Temperature: Avg AMBIENT Enclosure: STEEL

General technical data	
cable entry type	OH/UG
fastening method	SURFACE MOUNTING
number of openings	8
suitability for operation	COMMERCIAL
Electricity	
ampacity	200 A
supply voltage frequency rated value 50/60 Hz	No
Model	
product brand name	MURRAY
product type designation	HQU
special product feature	W/ LEVER BYPASS
Mechanical Design	
design of the terminal strip	7 TERMINALS
General product approval	
certificate of suitability	UL

last modified: 5/9/2023

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens