SIEMENS

Data sheet 6AG1422-1BL00-2AA0

SIPLUS S7-400 SM 422 32DO -25...+60°C based on 6ES7422-1BL00-0AA0



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	4 W
Digital outputs	
Number of digital outputs	32
Short-circuit protection	Yes; Clocked electronically
• Response threshold, typ.	0.7 to 1.5 A
Limitation of inductive shutdown voltage to	-27 V
Controlling a digital input	Yes; possible
Switching capacity of the outputs	

Subject to change without notice
© Copyright Siemens

• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	4 kΩ
Output voltage	
• for signal "1", min.	L+ (-0.3 V)
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "0" residual current, max.	0.3 mA
Output delay with resistive load	
• "0" to "1", max.	1 ms
• "1" to "0", max.	1 ms
Parallel switching of two outputs	
• for uprating	Yes; possible (only outputs of the same group)
• for redundant control of a load	Yes; possible (only outputs of the same group)
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• with inductive load (acc. to IEC 60947-5-1, DC13), max.	2 Hz; 2 Hz at 0.3 A; 0.5 Hz at 0.5 A
• on lamp load, max.	10 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	2 A; 8 adjacent outputs each
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m

Interrupts/diagnostics/status information	
Diagnostics function	No

Potential separation	
Potential separation digital outputs	
• between the channels	No
• between the channels, in groups of	32
• between the channels and backplane bus	Yes

Isolation	
Isolation tested with	500 V DC

Ambient conditions

Subject to change without notice
© Copyright Siemens

Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	60 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high availability
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection

Subject to change without notice
© Copyright Siemens

• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A

Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm

Weights	
Weight, approx.	600 g

last modified: 05/06/2020

Subject to change without notice
© Copyright Siemens