SIEMENS

RXD63B180



Documents

Cut Sheets 1

Speed Fax Sections 2

Adjustable Parameters

Adjustable pick-up value current / of instantaneous short-circuit trip unit / Full-scale value	10000 A
Adjustable pick-up value current / of instantaneous short-circuit trip unit / initial value	5000 A

Certificates

Certificate of suitability	UL489 / IEC 60947-2

Connections

Type of electrical connection / for main current circuit	VARIED CONNECTION ACCESSORIES

Electricity

Continuous current / rated value	1800 A

Environmental Conditions

Ambient temperature / during operation / minimum	-25 degC
Ambient temperature / during operation / maximum	75 degC

General Technical Data

Operating voltage / rated value / maximum	600 V

Mechanical Design

Size of the circuit-breaker	RD (2000A)
Height [in]	16 in
Width [in]	9 in
Depth [in]	6.19 in

Model

Product brand name	SIEMENS
Number of poles	3
Product designation	MOLDED CASE CIRCUIT BREAKER

Product sub brand name	SENTRON
Protective function of the overcurrent release	LI
Suitability for use	OVERLOAD AND SHORT CIRCUIT LINE PROTECTION
Design of the product	RD
Design of the overcurrent release	THERMAL - MAGNETIC

Switching Capacity According To Ul 489

Trip class	STANDARD
Maximum short-circuit current breaking capacity (Icu) / at 480 V / acc. to NEMA / rated value	50 kA
Maximum short-circuit current breaking capacity (Icu) / at 600 V / acc. to NEMA / rated value	25 kA
Maximum short-circuit current breaking capacity (Icu) / at 240 V / acc. to NEMA / rated value	65 kA

Speed Fax Sections 3

Delivery Information

Export Control Class	AL : N / ECCN : EAR99
Net Weight	59.8

Others 4

Additional Product Information

EAN/UPC	70783643247603
Country of Origin	MX, US
Commodity Code	8536200020
RoHS Compliance	*DQ

Speed Fax Sections 5

Product Selector Information

AC Interrupt Rating @ (kA)	System Voltage = 240V and Interrupt rating = 65 | System Voltage = 480V and Interrupt rating = 50 | System Voltage = 600V and Interrupt rating = 25
Frame Amps	2000
DC Interrupt Rating @ (kA)	System Voltage = 250V and Interrupt

	rating = 30 | System Voltage = 500V and Interrupt rating = 25
Trip Amps	1800
Poles	3
% Rated	80
Trip Type	Thermal Magnetic



Application and Selection Guide 6



Speed Fax Sections 7



Speed Fax Sections 8



Speed Fax Sections 9



Speed Fax Sections 10



Information and Instruction 11



Speed Fax Sections 12