SIEMENS

Data sheet US2:SN3048B1200P1



SIEMENS LOW VOLTAGE SN SERIES LOAD CENTER. FACTORY INSTALLED MAIN BREAKER WITH 30 1-INCH SPACES ALLOWING MAX 48 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A) 22KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS VALUE PACK, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	48
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200 A
voltage between phase and Ground (GND) rated value	120 V
voltage between phase and phase rated value	240 V
Model	
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM/ VALUE PACK
Mechanical Design	
number of modular width units for installation width	30
size of the circuit-breaker	200A
General product approval	
certificate of suitability	UL

last modified: 7/9/2021

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens