SIEMENS

Data sheet 3VA9987-0UA10



external function box EFB300 incl. connecting cable 1.5 m 3VA - EFB300
accessory for: 3VA20-26

Model	
product brand name	SENTRON
product designation	External function box EFB300
accessories	Digital input and output module
General technical data	
suitability for operation	Installation in fixed switchboard inside enclosed rooms
mounting position	any
degree of pollution	3
protection class IP	IP20 according to IEC60529
Voltage	
Rated control supply voltage Us with DC / maximal	24 V
Current	
product function	
● electronic tripping unit power supply	Yes
● digital input and output module	Yes
number of interfaces / of the circuit breaker communication system	1
number of higher-level circuit breakers / of the ZSI module	
● at input / maximum connectable	20
● at output / maximum connectable	8
design of the connecting cable / of the ZSI module	Flexible, shielded (at least 85% overlap), twisted cable, max. capacity: 200 nF/km (conductor/shield), 160 nF/km (conductor/conductor), inductivity 0.65 H/km, total line resistance: max. 28 ohms
number of digital inputs	1
input voltage / at digital input / at DC / rated value	24 V
operating range of digital input	IEC: SELV/ PELV
input voltage / at digital input	
● initial value for signal<1>-recognition	15 V
● full-scale value for signal<0> recognition	5 V
number of relay outputs	2
voltage / of the output relay	
● at AC / maximum	250 V
● at DC / maximum	250 V
operational current / of the output relay	
● at AC / at 250 V / rated value	6 A
● at DC / at 30 V / rated value	5 A
switching capacity current / of the output relay	
● at AC-12 / at 250 V	6 A
● at AC-15 / at 250 V	3 A
● at DC-12 / at 250 V	0.2 A

Subject to change without notice
© Copyright Siemens

● at DC-13 / at 250 V	0.1 A
output current / of the output relay	
● for signal <1> / initial value	10 mA
● for signal <1> / full-scale value	27 mA
● for signal <0> / maximum	0.2 mA
design of DIAZED fuse link / for short-circuit protection of auxiliary contacts of output relay	D0 6 A 500 V gL/gG
overvoltage category / of the output relay	III (relay) I (other)
number of static semiconductor outputs	2
voltage / of the static semiconductor outputs / at DC / rated value	24 V
voltage / of the static semiconductor outputs / at DC / rated value / note	IEC: SELV/ PELV
operational current / of the static semiconductor outputs / at DC / rated value	100 mA
power loss [V·A] / rated value	4 VA
control supply voltage / at DC / rated value / maximum	24 V
relative symmetrical tolerance / of the operating range of the control feed voltage	20 %
consumed current / maximum	0.16 A
Mechanical Design	
height	116 mm
width	70 mm
depth	36 mm
Net Weight	242.5 g
Connections	
type of electrical connection	removable/pluggable
type of electrical connection / at the inputs for supply voltage	screw-type terminals
connectable conductor cross-section / solid	
● minimum	0.5 mm²
● maximum	2.5 mm²
connectable conductor cross-section / finely stranded / with core end processing	
● minimum	0.5 mm²
● maximum	2.5 mm²
type of connectable conductor cross-sections / at the digital inputs / for AWG cables / solid	1x 21 to 14; 2x 21 to 16
tightening torque / with screw-type terminals / minimum	0.4 N·m
tightening torque / with screw-type terminals / maximum	0.5 N·m
Environmental conditions	
ambient temperature / during operation	
● minimum	-25 °C
● maximum	60 °C
ambient temperature / during transport	
● minimum	-25 °C
● maximum	80 °C
ambient temperature / during storage	
● minimum	-25 °C
● maximum	70 °C

Certificates

General Product Approval					EMV
CE EG-Konf.	UKCA	Confirmation	Miscellaneous	EAC	RCM

Test Certificates	Maritime application	other	Environment

Subject to change without notice
© Copyright Siemens


Type Test Certificates/Test Report | Confirmation | Miscellaneous | Environmental Confirmations

Environment


Environmental Confirmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9987-0UA10
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VA9987-0UA10
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9987-0UA10
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications



© Copyright Siemens



last modified: 7/18/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens