SIEMENS

Datasheet 6AV6671-5CE00-0AX1

CHARGING STATION FOR MOBILE PANEL 277(F) IWLAN WITH LOCK FOR CHARGE AND HOLD THE MOBILE PANEL 277(F) IWLAN CHARGING OF 2 SPARE BATTERIES



Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Rated current	3.2 A
Power	
Power	77 W
Degree and class of protection	
Enclosure according to EN 60529	IP65
Standards, approvals, certificates	
Certifications	CE, cULus, C-TICK
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
Ambient conditions	
Operating temperature	

Changes preserved
© Copyright Siemens AG

• Operation (vertical installation)	0 °C to +40 °C
— in vertical mounting position, minimum	0 °C
— in vertical mounting position, maximum	40 °C
Storage/transport temperature	
• Ambient temperature during storage, minimum	-20 °C
• Ambient temperature during storage, maximal	60 °C
• Transport, storage	-20 °C to +60 °C
Relative humidity	
• Operation, max.	85 %

Dimensions	
Width	208 mm
Height	333 mm
Depth	75 mm

Weights	
Weight (without packaging)	1.1 kg

other	
Usable in the following products	
• Product 1	6AV6645-0EB01-0AX1
• Product 2	6AV6645-0EC01-0AX1
• Product 3	6AV6645-0EF01-0AX1
• Product 4	6AV6645-0GB01-0AX1
• Product 5	6AV6645-0GC01-0AX1
• Product 6	6AV6645-0GF01-0AX1
• Product 7	6AV6645-0DD01-0AX1
• Product 8	6AV6645-0DE01-0AX1
• Product 9	6AV6645-0FD01-0AX1
• Product 10	6AV6645-0FE01-0AX1
• Product 11	6AV6645-0DB01-0AX0
• Product 12	6AV6645-0DC01-0AX0
• Product 13	6AV6645-0DD01-0AX0
• Product 14	6AV6645-0DE01-0AX0
last modified:	11.11.2014

Changes preserved
© Copyright Siemens AG