SIEMENS

Data sheet 3VL3522-1KN30-0AA0



circuit breaker VL250 UL type FG (cat no. NFK3B225) non-interchangeable frame, with circuit breaker approval acc. to UL 489 standard breaking capacity 3-pole; NEMA rating 35KA@480V and 18KA@600/347V (molded case circuit breaker) Electronic Trip Unit TM, LI TA=40°C In=225A, rated current II=1250...2500A short-circuit protection IR=225A Electronic Trip Unit for line protection without connection accessories without auxiliary release without auxiliary/alarm switch

Weight	2.3 kg
Net Weight	2.3 kg

General Product Approval

Confirmation				Miscellaneous	
	CCC	EG-Konf.			

other		Railway	Dangerous goods	Environment
Miscellaneous	Confirmation	Confirmation	Transport Information	Environmental Con-firmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3522-1KN30-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL3522-1KN30-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3522-1KN30-0AA0
CAx-Online-Generator
http://www.siemens.com/cax
Information- and Downloadcenter (catalogues, leaflets,...)
http://www.siemens.com/energy-automation





last modified: 3/17/2023

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens