SIEMENS

Data sheet 6EP1333-1LD00

SITOP PSU100D/1AC/24VDC/6.2A

********** spare part ********* PSU100D 24 V/6.2 A stabilized power supply input: 100-240 V AC output: 24 V DC/6.2 A



Input	
type of the power supply network	1-phase AC
supply voltage at AC	
● minimum rated value	100 V
● maximum rated value	240 V
● initial value	85 V
● full-scale value	264 V
design of input wide range input	Yes
operating condition of the mains buffering	at Vin = 115/230 V
buffering time for rated value of the output current in the event of power failure minimum	15 ms
operating condition of the mains buffering	at Vin = 115/230 V
line frequency	
● 1 rated value	50 Hz
● 2 rated value	60 Hz
line frequency	47 ... 63 Hz
input current	
● at rated input voltage 100 V	3.1 A
● at rated input voltage 240 V	2 A
current limitation of inrush current at 25 °C maximum	75 A
I2t value maximum	6.5 $A^2 \cdot s$
fuse protection type	internal
● in the feeder	Recommended miniature circuit breaker: from 10 A characteristic C or from 16 A characteristic B
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
● at output 1 at DC rated value	24 V
relative overall tolerance of the voltage	2 %
relative control precision of the output voltage	
● on slow fluctuation of input voltage	0.5 %
● on slow fluctuation of ohm loading	1 %
residual ripple	
● maximum	100 mV
voltage peak	
● maximum	100 mV
adjustable output voltage	22 ... 28 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer
display version for normal operation	Green LED for 24 V OK

Subject to change without notice
© Copyright Siemens

behavior of the output voltage when switching on	Overshoot of Vout < 2 %
response delay maximum	1 s
voltage increase time of the output voltage	
● maximum	30 ms
output current	
● rated value	6.2 A
● rated range	0 ... 6.2 A; +50 ... +70 °C: Derating 2.5%/K
supplied active power typical	150 W
product feature	
● bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	86 %
power loss [W]	
● at rated output voltage for rated value of the output current typical	24 W
Closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.5 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	5 %
Protection and monitoring	
design of the overvoltage protection	< 35 V
● typical	7.4 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Electronic shutdown, automatic restart
enduring short circuit current RMS value	
● typical	16 A
display version for overload and short circuit	-
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra low output voltage Vout according to EN 60950-1
operating resource protection class	Class I
leakage current	
● maximum	3.5 mA
● typical	1 mA
protection class IP	IP20
Approvals	
certificate of suitability	
● CE marking	Yes
● UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus (UL 60950-1, CSA C22.2 No. 60950-1), File E151273
● CSA approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus (UL 60950-1, CSA C22.2 No. 60950-1), File E151273
● NEC Class 2	No
● EAC approval	Yes
type of certification	
● BIS	Yes; R-611003204
● CB-certificate	Yes
certificate of suitability	
● IECEx	No
● ATEX	No
● ULhazloc approval	No
● cCSAus, Class 1, Division 2	No
● FM registration	No
certificate of suitability shipbuilding approval	No
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Lloyds Register of Shipping (LRS)	No
EMC	

Subject to change without notice
© Copyright Siemens

standard	
● for emitted interference	EN 55022 Class B
● for mains harmonics limitation	-
● for interference immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
● during operation	-10 ... +70 °C; with natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
Mechanics	
type of electrical connection	screw-type terminals
● at input	L, N, PE: 1 screw terminal each for 0.3 ... 1.3 mm² single-core/finely stranded
● at output	+, -: 2 screw terminals each for 0.3 ... 1.3 mm²
● for auxiliary contacts	-
width of the enclosure	97 mm
height of the enclosure	178 mm
depth of the enclosure	38 mm
required spacing	
● top	20 mm
● bottom	0 mm
● left	20 mm
● right	20 mm
net weight	0.55 kg
fastening method	Wall mounting
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

Subject to change without notice
© Copyright Siemens