SIEMENS

Data sheet 6EP3331-7SB00-0AX0



SITOP PSU6200/1AC/24VDC/1.3A

SITOP PSU6200 24 V/1.3 A Stabilized power supply Input: 120 - 230 V AC, (120 - 240 V DC) Output: 24 V DC/1.3 A

Input	
type of the power supply network	1-phase AC or DC
supply voltage at AC	
● minimum rated value	120 V
● maximum rated value	240 V
● initial value	85 V
● full-scale value	264 V
supply voltage	
● at DC	120 ... 240 V
input voltage	
● at DC	110 ... 275 V
design of input wide range input	Yes
overvoltage overload capability	300 V AC for 30 s
operating condition of the mains buffering	at Vin = 240 V
buffering time for rated value of the output current in the event of power failure minimum	150 ms
operating condition of the mains buffering	at Vin = 240 V
line frequency	
● 1 rated value	50 Hz
● 2 rated value	60 Hz
line frequency	47 ... 63 Hz
input current	
● at rated input voltage 120 V	0.6 A
● at rated input voltage 240 V	0.3 A
current limitation of inrush current at 25 °C maximum	32 A
fuse protection type	3.15 A
● in the feeder	Circuit breaker from 4 A characteristic C/6 A characteristic B to 16 A characteristic C or circuit breaker 3RV2011-1EA10 (setting 4 A) or 3RV2711-1ED10 (UL 489)
Output	
voltage curve at output	Controlled, isolated DC voltage
number of outputs	1
output voltage at DC rated value	24 V
output voltage	
● at output 1 at DC rated value	24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
● on slow fluctuation of input voltage	0.1 %
● on slow fluctuation of ohm loading	0.1 %
residual ripple	
● maximum	30 mV

Subject to change without notice
© Copyright Siemens

● typical	20 mV
voltage peak	
● maximum	30 mV
● typical	20 mV
adjustable output voltage	22.2 ... 26.4 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer; max. 31.2 W
display version for normal operation	Green LED for 24 V OK
behavior of the output voltage when switching on	Overshoot of Vout approx. 3 %
response delay maximum	1 s
voltage increase time of the output voltage	
● typical	50 ms
output current	
● rated value	1.3 A
● rated range	0 ... 1.3 A; +60 ... +70 °C: Derating 2.5%/K
supplied active power typical	31.2 W
short-term overload current	
● on short-circuiting during the start-up typical	1.3 A
● at short-circuit during operation typical	1.3 A
product feature	
● bridging of equipment	No
Efficiency	
efficiency in percent	86.3 %
power loss [W]	
● at rated output voltage for rated value of the output current typical	5 W
● during no-load operation maximum	0.8 W
Closed-loop control	
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	2 %
setting time	
● load step 10 to 90% typical	0.5 ms
● load step 90 to 10% typical	0.5 ms
● maximum	1 ms
Protection and monitoring	
design of the overvoltage protection	< 32 V
● typical	1.6 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Shutdown and periodic restart attempts
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra low output voltage Vout according to EN 60950-1
operating resource protection class	Class I
leakage current	
● maximum	3.5 mA
protection class IP	IP20
Approvals	
certificate of suitability	
● CE marking	Yes
● UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
● CSA approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
● cCSAus, Class 1, Division 2	No
● ATEX	No
certificate of suitability	
● IECEx	No
● NEC Class 2	Yes; acc. to UL 60950-1/UL 1310, File E151273
● ULhazloc approval	No
● FM registration	No
type of certification CB-certificate	Yes
certificate of suitability	

© Copyright Siemens

● EAC approval	Yes
● C-Tick	No
● Regulatory Compliance Mark (RCM)	Yes
type of certification BIS	Yes
certificate of suitability shipbuilding approval	Yes
shipbuilding approval	ABS; in process: DNV
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	Yes
● French marine classification society (BV)	No
● DNV GL	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No
EMC	
standard	
● for emitted interference	EN 55022 Class B
● for mains harmonics limitation	EN 61000-3-2
● for interference immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
● during operation	-25 ... +70 °C; with natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 … 95% no condensation
Mechanics	
type of electrical connection	push-in terminals
● at input	L1/+, L2/N/-, PE: push-in for 0.5 ... 2.5 mm² single-core/finely stranded
● at output	+1, -1, -2: push-in for 0.5 ... 2.5 mm²
● for auxiliary contacts	-
width of the enclosure	25 mm
height of the enclosure	100 mm
depth of the enclosure	88 mm
required spacing	
● top	50 mm
● bottom	50 mm
● left	0 mm
● right	0 mm
net weight	0.2 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
electrical accessories	Buffer module, redundancy module
mechanical accessories	Identification labels SIMATIC ET 200SP 6ES7193-6LF30-0AW0
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

Subject to change without notice
© Copyright Siemens