SIEMENS

Show actual product details

## Data sheet US2:HFC363SW

CSA 100A 3P 600V 3W FUSED HD TYPE 4X



| General technical data | |
|---|---|
| Installation location | INDUSTRIAL CORROSIVE RESISTANCE |
| Manner of function of the actuating element | SINGLE THROW |
| Mechanical service life (switching cycles) typical | 10000 |
| Mounting type | 2 OR 3 POINT MOUNTING HOLES |
| Number of poles | 3 |

| Electricity | |
|---|---|
| Ampacity | 100 A |
| Supply voltage frequency rated value 50/60 Hz | Yes |
| Voltage between phase and phase rated value | 600 V |

| Switching capacity | |
|---|---|
| Switching capacity active power | 3 W |

| Environmental conditions | |
|---|---|
| Ambient temperature during operation maximum | 120 °C |
| Ambient temperature during operation minimum | -20 °C |

| Model | |
|---|---|
| product brandname | SIEMENS |


Subject to change without notice
© Copyright Siemens AG

| | |
|---|---|
| Product type designation | ENCLOSED/SAFETY SWITCH |

## Mechanical Design

| | |
|---|---|
| Design of the housing | TYPE 4X |
| Material | SS |

## General product approval

| | |
|---|---|
| Certificate of suitability | CSA |

**last modified:** 01/09/2017


Subject to change without notice
© Copyright Siemens AG