SIEMENS

## Data sheet 8WD4458-6XB

LED, Base BA 15d, red, 230 V AC, accessory for signaling columns, with diameters 50 mm and 70 mm



Figure similar

| General technical data | |
|---|---|
| **product brand name** | SIRIUS |
| **product designation** | LED |
| **type of voltage of the operating voltage** | AC |
| **operating voltage** | |
| • 1 at AC at 50 Hz rated value | 230 V |
| • 1 at AC at 60 Hz rated value | 230 V |
| **relative positive tolerance of the operating voltage** | 10 % |
| **relative negative tolerance of the operating voltage** | -15 % |
| **color** | red |
| **reference code** | |
| • acc. to DIN EN 61346-2 | P |
| • acc. to DIN EN 81346-2 | P |

| Mechanical data | |
|---|---|
| **outer diameter of the signal column element** | 70 mm |

| Lamp |
|---|


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| type of light source | LED |
| light intensity | 1.44 cd |
| mounting type | BA 15d |

## Ambient conditions

| | |
|---|---|
| ambient temperature during operation | -20 ... +60 °C |
| height | 45 mm |
| width | 20 mm |

## Certificates/ approvals

| General Product Approval | EMC | Declaration of Conformity | other | |
|---|---|---|---|---|
| UL | RCM | EG-Konf. | Miscellaneous | Confirmation |

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,…)**
www.siemens.com/sirius/catalogs

**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4458-6XB

**Cax online generator**
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4458-6XB

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/8WD4458-6XB

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4458-6XB&lang=en

**last modified:** 09/24/2020


Subject to change without notice
© Copyright Siemens