Circuit Breakers

Type Q Plug-In Breakers

Selection and Ordering Data



Q115



Q215



Q315



Q1515NC



Q21515CTNC

Full Module (1" per pole) 10,000 A.I.C		
Ampere Rating	**Catalogue Number**	**Standard Package**
Single Pole		
15 20 25 30 40 50 60 70	**Q115**③ **Q120**③ **Q125** **Q130** **Q140** **Q150** **Q160** **Q170**	48
Two Pole Common Trip		
15 20 25 30 35 40 50 60	**Q215** **Q220** **Q225** **Q230** **Q235** **Q240** **Q250** **Q260**	24
70 80 90 100 110 125	**Q270** **Q280** **Q290** **Q2100** **Q2110** **Q2125**	5
150 200	**QN2150R**④⑤ **QN2200R**④⑤	1
Three Pole Common Trip		
15 20 25 30 40 50 60 70	**Q315** **Q320** **Q325** **Q330** **Q340** **Q350** **Q360** **Q370**	3
80 90 100	**Q380** **Q390** **Q3100**	2

Half Module (1/2" per pole) 10,000 A.I.C.			
Poles	**Amps**	**Catalogue Number**①	**Standard Package**
QT Dual (Twin)	15-15 15-20 15-30 15-40 20-15 20-20 30-15 30-20 30-30 40-15	**Q1515NC** **Q1520NC** **Q1530NC** **Q1540NC** **Q2015NC** **Q2020NC** **Q3015NC** **Q3020NC** **Q3030NC** **Q4015NC**	48

Quad Type (1/2" per pole) 10,000 A.I.C. Common Trip - centre poles only.			
Poles	**Ampere Rating**	**Catalogue Number**②	**Standard Package**
QT Quad	15-15 15-20 15-25 15-30 15-40	**Q21515CTNC** **Q21520CTNC** **Q21525CTNC** **Q21530CTNC** **Q21540CTNC**	24

① Typical catalogue number (ie. Q1515NC) represents two single-pole 15A circuit breakers - total width 1".

② Typical catalogue number (ie. Q21520CTNC) represents two single-pole, outer poles (two 15A 1-pole circuit breakers) and one 2-pole inner breaker with common trip (one 20A 2-pole circuit breaker) - total width 2".

③ Typical CSA Listed for frequent switching applications (SWD). 120V AC Fluorescent Lighting.

④ Requires 4 panel circuits, 2 adjacent and 2 opposite. Two twist outs should be only removed.

⑤ Will not fit in EQ3 or EQ4 loadcenters