SIEMENS

Q130HH

Certificates

Standard	UL LISTED / CSA / NOM CERTIFIED

Electricity

Continuous current / rated value	30 A
Voltage / between phase and Ground (GND) / rated value	120 V
Supply voltage frequency / rated value / 50/60 Hz	1

General Technical Data

Suitability for operation	ELECTRICAL DISTRIBUTION
Number of poles	1

Documents

Speed Fax Sections 1

Mechanical Design

Design of the product	HQP
Size of the circuit-breaker	QP (125A)
Design of the overload release	THERMAL - MAGNETIC
Height [in]	3.12 in
Width [in]	1 in
Depth [in]	3 in

Speed Fax Sections 2

Model

Product feature	65kA INTERRUPT
Type of electrical connection	PLUG-IN
Product brand name	SIEMENS
Type of connectable conductor cross-sections / at AWG conductors	14 - 6AWG (CU) / 12 - 6AWG (AL)
Type of mounting panel	LOADCENTER

Delivery Information

Export Control Class	AL : N / ECCN : EAR99
Net Weight	0.34

Product_Dimensions (LxWxH)	7.0X7.0X13.0

Additional Product Information

EAN/UPC	50783643148890
Country of Origin	MX
Commodity Code	8536200020
RoHS Compliance	*DQ

Product Selector Information

Amperage	30
Connection Style	PLUG ON STYLE
Frequency	60
Poles	1
UL Interrupt Rating (kA)	65
UL Voltage (V)	120



Speed Fax Sections 3



Speed Fax Sections 4



Speed Fax Sections 5



Brochures 6



Speed Fax Sections 7



Others 8



Speed Fax Sections 9



Speed Fax Sections 10