SIEMENS

Data sheet 8WD4448-6XE

LED, Base BA 15d, clear, 115 V AC, accessory for signaling columns, with diameters 50 mm and 70 mm



Figure similar

General technical data	
product brand name	SIRIUS
product designation	LED
type of voltage of the operating voltage	AC
operating voltage	
• 1 at AC at 50 Hz rated value	115 V
• 1 at AC at 60 Hz rated value	115 V
relative positive tolerance of the operating voltage	10 %
relative negative tolerance of the operating voltage	-15 %
color	clear
reference code	
• acc. to DIN EN 61346-2	P
• acc. to DIN EN 81346-2	P

Mechanical data	
outer diameter of the signal column element	70 mm

Lamp

Subject to change without notice
© Copyright Siemens

type of light source	LED
light intensity	3.42 cd
mounting type	BA 15d

Ambient conditions

ambient temperature during operation	-20 ... +60 °C
height	45 mm
width	20 mm

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity	other
UL EAC RCM EG-Konf.		Miscellaneous	Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4448-6XE

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4448-6XE

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/8WD4448-6XE

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4448-6XE&lang=en

last modified: 11/04/2020

Subject to change without notice
© Copyright Siemens