SIEMENS

Data sheet for SINAMICS V20

MLFB-Ordering data

6SL3210-5BB21-1BV1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input

Number of phases	1 AC
Line voltage	200 ... 240 V -15 % +10 %
Line frequency	47 ... 63 Hz

Output

Number of phases	3 AC
Rated voltage	230 V
Rated power (HO)	1.10 kW / 1.50 hp
Rated power (LO)	1.10 kW / 1.50 hp
Rated current (HO)	6.00 A
Rated current (LO)	6.00 A
Pulse frequency	8.00 kHz
Output frequency	0 ... 550 Hz

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s

General tech. specifications

Power factor λ	0.72
Offset factor cos φ	0.95
Efficiency η	0.98
Filter class (integrated)	Class B

Ambient conditions

Cooling	External fan
Installation altitude	1000 m (3281 ft)

Ambient temperature

Operation	-10 ... 60 °C (14 ... 140 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity

Max. operation	95 %

Communication

Communication	USS, Modbus RTU

Standards

Compliance with standards	CE, cULus, C-Tick (RCM)
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3

SIEMENS

Data sheet for SINAMICS V20

MLFB-Ordering data **6SL3210-5BB21-1BV1**



Figure similar

Mechanical data

Mounting position	Wall mounting / side-by-side mounting
Degree of protection	IP20 / UL open type
Size	FSAC
Net weight	1.40 kg (3.09 lb)
Width	91.0 mm (3.57 in)
Height	160.9 mm (6.33 in)
Depth	147.0 mm (5.79 in)

Inputs / outputs

Standard digital inputs

Number	4

Digital outputs

Number as relay changeover contact	1
Number as transistor	1

Analog inputs

Number	2 (Can be used as additional digital input)

Analog outputs

Number	1

Connections

Max. motor cable length

Shielded	25 m (82 ft)
Unshielded	50 m (164 ft)