SIEMENS

## Data sheet 4AV3502-2FB00-0A



Figure similar

POWER SUPPLY; PHASES:3; PN(KW):1,08; UPRI(V):575(600)-500-460(480)- 400(415)-230(240)-200; USEC(V DC):24; ISEC(A DC):45/54 (60/40 CEL); F(HZ):50...60; VECTOR GR./SHIELD WNG.:YY0 /0; PROTECTION CL.:I; TA/ISOKL:60 /B; W(%):4,2; IP00; TYPE OF TERMINALS:SCREW CONNECTION; INSTALLATION:SCREW; EN 61558-2-6, EN61131-2 >SAFETY ISOLATING TRANSFORMER<

| General technical data | | |
|---|---|---|
| **Product designation** | | 4AV3502-2FB00-0A |
| **Product brand name** | | SIDAC |
| **Vector group** | | Yy0 |
| **Certificate of suitability** | | CE |
| **Product function** | | |
| • Temperature monitoring | | No |
| • Insulation monitoring | | No |
| • Short-circuit and overload proof | | No |
| • varistor protective wiring | | Yes |
| **Operating resource protection class** | | I |
| **Number of shielding windings** | | 0 |

| Inputs | | |
|---|---|---|
| **Phase number of the inputs** | | 3 |
| **Type of current of the inputs** | | AC |
| **Input voltage** | | |
| • _1 rated value | V | 575 |


Subject to change without notice
© Copyright Siemens

| | | |
|---|---|---|
| • _2 rated value | V | 500 |
| • _3 rated value | V | 460 |
| • _4 rated value | V | 400 |
| • _5 rated value | V | 230 |
| • _6 rated value | V | 200 |
| **Electrical input frequency** | | |
| • minimum | Hz | 50 |
| • maximum | Hz | 60 |
| **Input voltage** | | |
| • minimum | V | 180 |
| • maximum | V | 609.5 |
| **Input current** | | |
| • _1 rated value | A | 1.4 |
| • _2 rated value | A | 1.6 |
| • _3 rated value | A | 1.7 |
| • _4 rated value | A | 2 |
| • _5 rated value | A | 3.4 |
| • _6 rated value | A | 3.9 |
| **Type of electrical connection at input for main current circuit** | | screw-type terminals |

## Outputs

| | | |
|---|---|---|
| **Type of current** | | |
| • _1 at output | | DC |
| **Output voltage** | | |
| • _1 rated value | V | 24 |
| **Output voltage of the measurement signal at analog output at DC maximum** | V | 28.8 |
| **Output voltage of the measurement signal at analog output at DC minimum** | V | 20.4 |
| **Output current** | | |
| • _1 rated value | A | 45 |
| **Type of electrical connection at output for main current circuit** | | screw-type terminals |
| **Relative residual ripple** | | |
| • of the output voltage 1 for main current circuit maximum | % | 5 |

## Ambient conditions

| | | |
|---|---|---|
| **Thermal class acc. to IEC 60085** | | B |
| **Ambient temperature rated value** | °C | 60 |
| **Protection class IP** | | IP00 |

## Mechanical data

| | | |
|---|---|---|
| **Mounting type** | | screws |


Subject to change without notice
© Copyright Siemens

| | | |
|---|---|---|
| **Construction form of the iron core** | | 3UI 114/62 |
| **Width** | m | 0.266 |
| **Height** | m | 0.26 |
| **Depth** | m | 0.19 |

## Certificates/ approvals

| General Product Approval | | | Declaration of Conformity | Shipping Approval | other |
|---|---|---|---|---|---|
| UL | | EG-Konf. | Miscellaneous | PRS | Confirmation |

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/ic10

**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AV3502-2FB00-0A

**Cax online generator**
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4AV3502-2FB00-0A

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/4AV3502-2FB00-0A

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4AV3502-2FB00-0A&lang=en

**last modified:** 07/28/2020


Subject to change without notice
© Copyright Siemens