SIEMENS

US2:LGB3B050B



Certificates

Standard	UL / CSA / IEC / NOM

Electricity

Voltage / between phase and Ground (GND) / rated value	347 V
Continuous current / rated value	50 A
Tripping characteristic class	VERY HIGH 0
Voltage / between phase and phase / rated value	600 V

General Technical Data

Number of poles	3 0
Suitability for operation	ELECTRICAL DISTRIBUTION
Mounting type	PANELBOARD BUS

Mechanical Design

Depth [in]	2.8 in
Design of the product	MOLDED CASE CIRCUIT BREAKER
Width [in]	3 in
Height [in]	5.4 in
Design of the overload release	THERMAL - MAGNETIC

Model

Product feature	STANDARD 40C CALIBRATION
Type of electrical connection	BOLT-ON (LOW-TAB)
product brandname	SIEMENS
Type of connectable conductor cross-sections / at AWG conductors / for load-side outgoing feeder / single or multi-stranded	8 - 1/0 AWS (CU/AL)

Delivery Information

Documents

Speed Fax Sections 1

Information and Instruction 2

Export Control Class	AL : N / ECCN : EAR99
Net Weight	2.75
Product_Dimensions (LxWxH)	3.0X3.0X5.0

Additional Product Information

EAN/UPC	50887621220285
Country of Origin	MX
Commodity Code	8536200020
RoHS Compliance	*DQ