SIEMENS

# Data sheet for SINAMICS G120X

## Article No. : 6SL3220-1YE38-0UF0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

## Rated data

### Input

| | | |
|---|---|---|
| Number of phases | 3 AC | |
| Line voltage | 380 ... 480 V +10 % -20 % | |
| Line frequency | 47 ... 63 Hz | |
| **Rated voltage** | **400V IEC** | **480V NEC** |
| Rated current (LO) | 86.00 A | 74.00 A |
| Rated current (HO) | 78.00 A | 69.00 A |

### Output

| | | |
|---|---|---|
| Number of phases | 3 AC | |
| **Rated voltage** | **400V IEC** | **480V NEC** [1] |
| Rated power (LO) | 45.00 kW | 60.00 hp |
| Rated power (HO) | 37.00 kW | 50.00 hp |
| Rated current (LO) | 90.00 A | 77.00 A |
| Rated current (HO) | 75.00 A | 65.00 A |
| Rated current (IN) | 93.00 A | |
| Max. output current | 122.00 A | |
| Pulse frequency | 4 kHz | |
| Output frequency for vector control | 0 ... 200 Hz | |
| Output frequency for V/f control | 0 ... 550 Hz | |

### Overload capability

Low Overload (LO)

110% base load current IL for 60 s in a 300 s cycle time

High Overload (HO)

150% x base load current IH for 60 s within a 600 s cycle time

## General tech. specifications

| | |
|---|---|
| Power factor λ | 0.90 ... 0.95 |
| Offset factor cos φ | 0.99 |
| Efficiency η | 0.97 |
| Sound pressure level (1m) | 70 dB |
| Power loss [3] | 1.340 kW |
| Filter class (integrated) | Unfiltered |
| EMC category (with accessories) | without |
| Safety function "Safe Torque Off" | without SIRIUS device (e.g. via S7-1500F) |

## Communication

| | |
|---|---|
| Communication | PROFINET, EtherNet/IP |

## Inputs / outputs

### Standard digital inputs

| | |
|---|---|
| Number | 6 |
| Switching level: 0 → 1 | 11 V |
| Switching level: 1 → 0 | 5 V |
| Max. inrush current | 15 mA |

### Fail-safe digital inputs

| | |
|---|---|
| Number | 1 |

### Digital outputs

| | |
|---|---|
| Number as relay changeover contact | 2 |
| Output (resistive load) | DC 30 V, 5.0 A |
| Number as transistor | 0 |

### Analog / digital inputs

| | |
|---|---|
| Number | 2 (Differential input) |
| Resolution | 10 bit |

### Switching threshold as digital input

| | |
|---|---|
| 0 → 1 | 4 V |
| 1 → 0 | 1.6 V |

### Analog outputs

| | |
|---|---|
| Number | 1 (Non-isolated output) |

### PTC/ KTY interface

1 motor temperature sensor input, sensors that can be connected PTC, KTY and Thermo-Click, accuracy ±5 °C

## Closed-loop control techniques

| | |
|---|---|
| V/f linear / square-law / parameterizable | Yes |
| V/f with flux current control (FCC) | Yes |
| V/f ECO linear / square-law | Yes |
| Sensorless vector control | Yes |
| Vector control, with sensor | No |
| Encoderless torque control | No |
| Torque control, with encoder | No |

SIEMENS

## Data sheet for SINAMICS G120X

**Article No. :** **6SL3220-1YE38-0UF0**

### Ambient conditions

| | |
|---|---|
| Standard board coating type | Class 3C2, according to IEC 60721-3-3: 2002 |
| Cooling | Air cooling using an integrated fan |
| Cooling air requirement | 0.083 m³/s (2.931 ft³/s) |
| Installation altitude | 1,000 m (3,280.84 ft) |
| **Ambient temperature** | |
| Operation | -20 ... 45 °C (-4 ... 113 °F) |
| Transport | -40 ... 70 °C (-40 ... 158 °F) |
| Storage | -25 ... 55 °C (-13 ... 131 °F) |
| **Relative humidity** | |
| Max. operation | 95 % At 40 °C (104 °F), condensation and icing not permissible |

### Connections

| | |
|---|---|
| **Signal cable** | |
| Conductor cross-section | 0.15 ... 1.50 mm² (AWG 24 ... AWG 16) |
| **Line side** | |
| Version | screw-type terminal |
| Conductor cross-section | 25.00 ... 70.00 mm² (AWG 6 ... AWG 3/0) |
| **Motor end** | |
| Version | Screw-type terminals |
| Conductor cross-section | 25.00 ... 70.00 mm² (AWG 6 ... AWG 3/0) |
| **DC link (for braking resistor)** | |
| PE connection | Screw-type terminals |
| **Max. motor cable length** | |
| Shielded | 200 m (656.17 ft) |
| Unshielded | 300 m (984.25 ft) |

### Mechanical data


| | |
|---|---|
| Degree of protection | IP20 / UL open type |
| Frame size | FSE |
| Net weight | 27 kg (59.52 lb) |
| **Dimensions** | |
| Width | 275 mm (10.83 in) |
| Height | 551 mm (21.69 in) |
| Depth | 248 mm (9.76 in) |

### Standards

| | |
|---|---|
| Compliance with standards | UL, cUL, CE, C-Tick (RCM), EAC, KCC, SEMI F47, REACH |
| CE marking | EMC Directive 2004/108/EC, Low-Voltage Directive 2006/95/EC |

### Converter losses to IEC61800-9-2*

| | |
|---|---|
| Efficiency class | IE2 |
| Comparison with the reference converter (90% / 100%) | 45.1 % |




The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*calculated values

[1] The output current and HP ratings are valid for the voltage range 440V-480V

[3] Typical value. More information can be found in the element group "Converter losses to IEC 61800-9-2" in this datasheet.