SIEMENS

# Q3100HH




## Documents

Speed Fax Sections 1

Speed Fax Sections 2

## Certificates

| | |
|---|---|
| Standard | UL LISTED / CSA / NOM CERTIFIED |

## Electricity

| | |
|---|---|
| Supply voltage frequency / rated value / 50/60 Hz | 1 |
| Continuous current / rated value | 100 A |
| Voltage / between phase and phase / rated value | 240 V |

## General Technical Data

| | |
|---|---|
| Suitability for operation | ELECTRICAL DISTRIBUTION |
| Number of poles | 3 |

## Mechanical Design

| | |
|---|---|
| Width [in] | 3 in |
| Design of the product | HQP |
| Design of the overload release | THERMAL - MAGNETIC |
| Height [in] | 3.12 in |
| Depth [in] | 3 in |
| Size of the circuit-breaker | QP (125A) |

## Model

| | |
|---|---|
| Product brand name | SIEMENS |
| Type of connectable conductor cross-sections / at AWG conductors | 4 - 1/0AWG (CU) / 2 - 1/0AWG (AL) |
| Type of mounting panel | LOADCENTER |
| Product feature | 65kA INTERRUPT |
| Type of electrical connection | PLUG-IN |

## Delivery Information

| | |
|---|---|
| Export Control Class | AL : N / ECCN : EAR99 |
| Net Weight | 1.08 |

| | |
|---|---|
| Product_Dimensions (LxWxH) | 7.0X8.0X13.0 |

## Additional Product Information

| | |
|---|---|
| EAN/UPC | 50783643149101 |
| Country of Origin | MX |
| Commodity Code | 8536200020 |
| RoHS Compliance | *DQ |

Brochures 3

Speed Fax Sections 4

Information and Instruction 5