SIEMENS

HJXD63B200L

Adjustable Parameters

Adjustable pick-up value current / of instantaneous short-circuit trip unit / initial value	1250 A
Adjustable pick-up value current / of instantaneous short-circuit trip unit / Full-scale value	2500 A

Certificates

Certificate of suitability	UL489 / IEC 60947-2

Connections

Type of electrical connection / for main current circuit	MECHANICAL LUGS

Electricity

Continuous current / rated value	200 A

Environmental Conditions

Ambient temperature / during operation / minimum	-25 degC
Ambient temperature / during operation / maximum	75 degC

General Technical Data

Operating voltage / rated value / maximum	600 V

Mechanical Design

Size of the circuit-breaker	JD (400A)
Height [in]	11 in
Width [in]	7.5 in
Depth [in]	4 in

Model

Suitability for use	OVERLOAD AND SHORT CIRCUIT LINE PROTECTION
Design of the product	JD

Documents

Application and Selection Guide 1

Cut Sheets 2

Design of the overcurrent release	THERMAL - MAGNETIC
Product brand name	SIEMENS
Number of poles	3
Product designation	MOLDED CASE CIRCUIT BREAKER
Product sub brand name	SENTRON
Protective function of the overcurrent release	LI

Switching Capacity According To Ul 489

Trip class	HIGH
Maximum short-circuit current breaking capacity (Icu) / at 600 V / acc. to NEMA / rated value	35 kA
Maximum short-circuit current breaking capacity (Icu) / at 240 V / acc. to NEMA / rated value	100 kA
Maximum short-circuit current breaking capacity (Icu) / at 480 V / acc. to NEMA / rated value	65 kA

Information and Instruction 3

Delivery Information

Export Control Class	AL : N / ECCN : EAR99
Net Weight	14.0

Others 4

Additional Product Information

EAN/UPC	70783643084642
Country of Origin	MX, US
Commodity Code	8536200020
RoHS Compliance	*DQ

Product Selector Information

AC Interrupt Rating @ (kA)	System Voltage = 240V and Interrupt rating = 100 | System Voltage = 480V and Interrupt rating = 65 | System Voltage = 600V and Interrupt rating = 35
Frame Amps	400
DC Interrupt Rating @ (kA)	System Voltage = 500V and Interrupt rating = 35

Cut Sheets 5

Trip Amps	200
Poles	3
% Rated	80
Trip Type	Thermal Magnetic