# 6SL35326DF710RA2

Industrial automation components

Add to quote

Ask about this product




| | |
|---|---|
| **Manufacturer** | Siemens |
| **Catalog number** | 6sl35326df710ra2 |
| **Category** | Industrial automation components |
| **Product type** | Industrial automation components |
| **Status** | Active product |

## Technical specification

| | |
|---|---|
| **Customs Tariff Code** | 85015220 |
| **EAN** | 4034106440633.0 |
| **eClass 6** | 27-02-31-01 |
| **eClass 7.1** | 27-02-31-01 |
| **eClass 8** | 27-02-31-01 |
| **eClass Version 9** | 27-02-31-01 |
| **eClass Version 9.1** | 27-02-31-01 |
| **Quantity in Package** | 1 |
| **Packaging Length** | 0,00 |
| **Packaging Width** | 0,00 |
| **Packaging Height** | 0,00 |
| **Product Code** | 5185 |
| **Comparative Metals Coefficient** | 03.06.2015 |
| **UPC** | 887621880354.0 |
| **Weight** | 4100 kg |
| **Product ID** | 6SL3532-6DF71-0RA2 |
| **Notes** | Wycofanie produktu od: 01.10.2023 |

**Automation Trader**
960 Capability Green
Luton, Bedfordshire LU1 3PE
VAT ID: PL6463009354
REGON: 527345886
DUNS: 427734105
BDO: 000726360

**Phone**
+44 7418 359 399

**Email**
info@automationtrader.com

Generated on demand. The PDF file is not stored on the server.

| | |
|---|---|
| **AL Field** | N |
| **Compliance** | Produkt zgdony z RoHS od: 03.06.2015 |
| **Configurable Product** | False |
| **Country of Origin** | DE |
| **ECCN** | N |
| **ETIM 7** | EC001857 |
| **Group Classification Key** | R220 |
| **List of Characteristics** | D21MC |
| **Product Description** | DISTRIBUTED SERVO-DRIVE SINAMICS S120M AH36, M(0)=1,00Nm, n(n)=3000 RPM, INPUT: DC 600V ABSOLUTE ENCODER 20 BIT NATURAL AIR COOLING, IM B5, IM V1, IM V3 DEGREE OF PROTECTION: IP65 ON SHAFT END IP67 SHAFT WITH FITTED KEY TOLERANCE N; W/O HOLDING BRAKE |
| **Unit of Measure** | ST |

## Description

The DISTRIBUTED SERVO-DRIVE SINAMICS S120M AH36 is an advanced drive device that offers a nominal torque of 1.00 Nm and a rotational speed of up to 3000 RPM. Powered by DC 600V, it features a 20-bit absolute encoder for precise control. The device is naturally air-cooled and has an IP65 protection rating at the shaft end and IP67 on the shaft with a fitted key. This product is RoHS compliant since 03.06.2015 and is not configurable. It weighs 4100 g and is manufactured in Germany.