SIEMENS

Data sheet US2:HF262



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600V A. Rating: 60A Wattage: 2W No. Of Poles: 2P F. Rating: 60Hz Action: SINGLE THROW Material: STEEL Enclosure: TYPE 1. 2-3 point mounting holes. O. Cycles: 10000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDOOR

Installation location	INDOOR
Manner of function of the actuating element	SINGLE THROW
Mechanical service life (switching cycles) typical	10000
Mounting type	2 OR 3 POINT MOUNTING HOLES
Number of poles	2

Electricity	
Ampacity	60 A
Supply voltage frequency rated value 50/60 Hz	Yes
Voltage between phase and phase rated value	600 V

Switching capacity	
Switching capacity active power	2 W

Environmental conditions	
Ambient temperature during operation maximum	120 °C
Ambient temperature during operation minimum	-20 °C

Model	
Product brand name	SIEMENS
Product type designation	ENCLOSED/SAFETY SWITCH

Subject to change without notice
© Copyright Siemens

Mechanical Design	
Design of the housing	TYPE 1
Material	STEEL

General product approval	
Certificate of suitability	UL

last modified: 05/28/2019

Subject to change without notice
© Copyright Siemens