SIEMENS

Data sheet 6ES7141-6BF00-0AB0



SIMATIC DP, ET 200ECO PN, 8 DI 24 V DC; 4xM12, Duplicate assignment, Degree of protection IP67

General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	Yes
Input current	
Current consumption, typ.	100 mA
from supply voltage 1L+, max.	4 A
Encoder supply	
Number of outputs	4
24 V encoder supply	
● Short-circuit protection	Yes; Electronic
● Output current, max.	100 mA; per output
Power loss	
Power loss, typ.	5.5 W
Digital inputs	
Number of digital inputs	8
● in groups of	2
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 60 °C, max.	8
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	-3 to +5V
● for signal "1"	+11 to +30V
Input current	
● for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	typically 3 ms
— at "1" to "0", max.	typically 3 ms
Cable length	
● unshielded, max.	30 m
Encoder	
Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA

Subject to change without notice
© Copyright Siemens

Interfaces	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
1. Interface	
Interface types	
● M12 port	Yes
● integrated switch	Yes
Interface types	
M12 port	
● Autonegotiation	Yes
● Autocrossing	Yes
● Transmission rate, max.	100 Mbit/s
Protocols	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No
PROFINET IO Device	
Services	
— IRT with the option "high flexibility"	Yes
— Prioritized startup	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
Open IE communication	
● TCP/IP	No
● SNMP	Yes
● DCP	Yes
● LLDP	Yes
● ping	Yes
● ARP	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Diagnostic information readable	Yes
● Monitoring the supply voltage	Yes; green "ON" LED
● Wire-break in signal transmitter cable	Yes
● Short-circuit encoder supply	Yes; Per channel group
● Group error	Yes; Red/yellow "SF/MT" LED
Potential separation	
between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
Potential separation channels	
● between the channels	No
Isolation	
tested with	
● 24 V DC circuits	707 V DC (type test)
● Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3
Degree and class of protection	
IP degree of protection	IP65/67
connection method	
Design of electrical connection	4/5-pin M12 circular connectors
Dimensions	
Width	30 mm
Height	200 mm
Depth	49 mm
Weights	
Weight, approx.	550 g

Subject to change without notice
© Copyright Siemens

last modified:	8/16/2023

Subject to change without notice
© Copyright Siemens