SIEMENS

Data sheet 6GK5908-0PB00

product type designation	**KEY-PLUG SINEMA RC**
product description	Removable medium for activating SINEMA RC for SCALANCE M-800 / S615 and for simple device replacement in the event of a fault
	KEY-PLUG SINEMA RC, Removable data storage medium for enabling of the connection to SINEMA Remote Connect for S615 and SCALANCE M for simple device replacement in event of fault and for Recording of configuration data.



suitability for use	Activation of SINEMA RC
ambient conditions	
ambient temperature	
● during operation	-40 ... +75 °C
● during storage	-40 ... +80 °C
● during transport	-40 ... +80 °C
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
width	24.3 mm
height	17 mm
depth	8.1 mm
net weight	5 g
design of the removable storage	
● C-PLUG	No
● KEY-PLUG	Yes
product features, product functions, product components / general	
storage capacity	256 Mibyte
standards, specifications, approvals	
reference code	
● according to IEC 81346-2:2019	CFA
further information / internet-Links	
Internet-Link	
● to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
● to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
● to the website: IWLAN	http://www.siemens.com/iwlan
● to website: Industrial communication	http://www.siemens.com/simatic-net
● to website: Industry Mall	https://mall.industry.siemens.com
● to website: Information and Download Center	http://www.siemens.com/industry/infocenter
● to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
● to website: Image database	http://automation.siemens.com/bilddb
● to website: CAx-Download-Manager	http://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
last modified:	5/20/2021

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens