SIEMENS

Data sheet 6ES7223-1BL22-0XA0

SIMATIC S7-200, DIGITAL I/O EM 223, FOR S7-22X CPU ONLY, 16DI 24V DC, SINK/SOURCE, 16DO 24V DC, 0.75A/POINT,SOURCE



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	160 mA
Power loss	
Power loss, typ.	6 W
Digital inputs	
Number of digital inputs	16
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	0 to 5 V
• for signal "1"	15V DC to 30V DC
Input current	

Changes preserved
© Copyright Siemens AG

• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	4.5 ms
Digital outputs	
Number of digital outputs	16
Short-circuit protection	No
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "0", max.	0.1 V
• for signal "1", min.	20 V
Output current	
• for signal "1" rated value	750 mA
Total current of the outputs (per group)	
all mounting positions	
— Current per conductor/group, max.	3 A; 3 / 3 / 6
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	0.75 A; each output
— on lamp load, max.	5 W
— with resistive load, max.	0.75 A; each output
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
Potential separation	
Potential separation digital inputs	
• Potential separation digital inputs	Yes; Optocoupler
• between the channels, in groups of	4
Potential separation digital outputs	
• Potential separation digital outputs	Yes; Optocoupler
• between the channels, in groups of	4; 4 / 4 / 8
Isolation	
Isolation tested with	500 V AC
Connection method	
Plug-in I/O terminals	Yes

Changes preserved
© Copyright Siemens AG

Dimensions	
Width	137.5 mm
Height	80 mm
Depth	62 mm

Weights	
Weight, approx.	360 g

last modified: 08.08.2015

Changes preserved
© Copyright Siemens AG