
SIEMENS

Data sheet 6AV6640-0BA11-0AX0

SIMATIC OPERATOR PANEL OP 73MICRO FOR SIMATIC S7-200 3" LC DISPLAY, BACKLIT WITH GRAPHICS CAPABILITY CONFIGURABLE WINCC FLEXIBLE 2004 MICRO HSP UPWARDS; CONTAINS OPEN-SOURCE-SW, WHICH IS PROVIDED FREE OF CHARGE. FOR DETAILS SEE ENCLOSED CD



General information	
Customer-specific configuration	No
Display	
Design of display	STN
Screen diagonal	3 in
Number of colors	2
Color type	Black/white
Resolution (pixels)	
• Horizontal image resolution	160 Pixel
• Vertical image resolution	48 Pixel
• Resolution (WxH in pixel)	160 x 48
Backlighting	
• MTBF backlighting (at 25 °C)	100 000 h
Control elements	
Control elements	Membrane keyboard
Keyboard fonts	
• Membrane keyboard	
— user-definable label membrane keys	No

Changes preserved
© Copyright Siemens AG

• Function keys	
— Number of function keys	4
— Number of function keys with LEDs	0
• Keys with LED	Yes
• Numeric/alphabetical input	Yes / Yes
— hexadecimal keyboard	Yes
• Multi-key operation	Yes
Touch operation	
• Design as touch screen	No
Connection type	
• Connection for mouse/keyboard/barcode reader	- / - / -
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	80°
Supply voltage	
Type of supply voltage	DC
Input current	
Current consumption (rated value)	0.1 A
Starting current inrush I²t	0.5 A²·s
Processor	
Processor type	ARM
Memory	
Type of memory	Flash
Time of day	
Clock	
• Type	Software clock, no battery backup
• Hardware clock (real-time clock)	No
• Software clock	Yes
• retentive	No
• synchronizable	No
Interfaces	
Interfaces/bus type	1 x RS485 (max. 187.5 Mbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	187.5 kbit/s
Degree and class of protection	
Front	IP65, NEMA 4x (when installed)
IP (at the front)	IP65

Changes preserved
© Copyright Siemens AG

IP (rear)	IP20

Standards, approvals, certificates	
Certifications	CE, GL, ABS, BV, DNV, LRS, UL, CSA, cULus, C-TICK, NEMA 4x
cULus	Yes
EAC (formerly Gost-R)	No
Suitable for safety functions	No
Marine approval	
• Germanischer Lloyd (GL)	Yes
• American Bureau of Shipping (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (Class NK)	Yes
• Polski Rejestr Statkow (PRS)	No
Use in hazardous areas	
• EX zone 2	No
• EX zone 22	No
• FM Class I Division 2	No

Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	90 %

Operating systems	
Operating system	LINUX

Configuration	
Configuration software	
• STEP 7 Basic (TIA Portal)	No
• STEP 7 Professional (TIA Portal)	No
• WinCC flexible Compact	Yes
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	Yes
• WinCC Basic (TIA Portal)	No
• WinCC Comfort (TIA Portal)	No
• WinCC Advanced (TIA Portal)	No

Changes preserved
© Copyright Siemens AG

• WinCC Professional (TIA Portal)	No
• Configuration tool	WinCC flexible Micro Version 2004 SP1, HSP or higher (to be ordered separately)
• 2. Configuration kit	WinCC flexible Micro
— Version	Version 2004 SP 1; HSP
— Configuration tool	WinCC flexible
— Type	Micro

Languages	
Online languages	
• Number of online/runtime languages	5
Project languages	
• Languages per project	32

Functionality under WinCC (TIA Portal)	
Libraries	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	320
• Number of tooltips	0
Message system	
• Number of alarm classes	32
• Number of messages	250
• Bit messages	Yes
— Number of bit messages	250
• Analog messages	Yes
— Number of analog messages	5
• Telegram message procedure Alarm S	No
• System messages HMI	Yes
• System messages PLC	Yes
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No
• Message length (in characters)	80
• Number of process values per message	8
• Message indicator	Yes
• acoustic feedback	No
• First/last value	Yes
Variables	
• Number of variables per device	500
• Number of variables per screen	20
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes

Changes preserved
© Copyright Siemens AG

Images	
• Number of configurable images	250
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	No
• Image number in the PLC	No
Image objects	
• Text objects	1,000 text elements
• Number of I/O fields per image	20
• Number of date/time fields	0
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, icons, icon (full-screen)
— Icons	250
— Icon (full screen)	25
Complex image objects	
• Status/control	Not possible
• dynamic objects	Bar graphs
— Number of curve diagrams per image	0
• Number of bars per chart	5
• Limit value lines	Yes
• alphanumeric fields	0
• alphanumeric fields per image	0
• numerical fields	0
• numerical fields per image	0
• Password fields	0
• Number of slides per image	0
• Number of analog indicators per image	0
• Number of visible switches per project	0
• visible switches per image	0
• hidden switches per image	0
• Number of status switches per project	0
• Number of selector switches per project	0
• Selector switches per image	0
• Number of decade switches per project	0
• Decade switches per image	0
• Number of signal lamps per project	0
• Signal lamps per image	0
Attributes for dynamic objects	
• Color change	No
• X/Y movement	No

Changes preserved
© Copyright Siemens AG

• Hide	Yes
• Angle of rotation	No
Lists	
• Number of text lists per project	150
• Number of graphics lists per project	0
Security	
• Number of user groups	1
• Number of users	1
• Password export/import	Yes
Transfer (upload/download)	
• Transfer of configuration	serial
Process coupling	
• Connection to controller	for S7-200, see section on "System interfaces"
• S7-200	Yes
— PPI (point-to-point)	Yes
— PPI network	Yes
— MPI	Yes
— PROFIBUS DP	No
• S5	No
— serial	No
— PROFIBUS DP	No
• TI 505	No
• Allen Bradley (DF1)	No
• Allen Bradley (DF485)	No
• Mitsubishi (FX)	No
• Mitsubishi (MP4)	No
• Telemecanique (ADJUST)	No
• Telemecanique (Uni-Telway)	No
• OMRON (LINK/Multilink)	No
• Modicon (Modbus)	No
• GE-Fanuc (SNP)	No
Functions	
• Key repeat	Yes
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	No
• Menu tree editor	No
• Unit switchover	No
Service tools/configuration aids	
• Clean screen	No
• Touch calibration	No

Changes preserved
© Copyright Siemens AG

• Backup/Restore manually	Yes
• Simulation	No
• Device switchover	Yes
• Delta transfer	No
• Monitoring function for battery and memory	No
• Trace (operation archive)	No
Expandability/openness	
• Open Platform Program	No

Peripherals/Options	
Peripherals	
• Multimedia Card	No

Dimensions	
Width of the housing front	154 mm
Height of housing front	84 mm
Mounting cutout, width	138 mm
Mounting cutout, height	68 mm
Overall depth	28.5 mm

Weights	
Weight (without packaging)	0.25 kg

Other	
free hotline	Yes
Warranty period	1 y

last modified: 08.08.2015

Changes preserved
© Copyright Siemens AG