SIEMENS

Data sheet 7PG2111-1DA30-0DB0



Figure similar

RELAY SOLKOR RF CIRCULATING CURRENT/FEEDER PROTECTION IMPROVED DIFFER. CURRENT FEEDER PROTECTION USING PILOT WIRES, FASTER OPERATING TIME, PILOT LOOP RESISTANCE 2000 OHMS MAX. STANDARD INSULATION LEVEL 5KV PILOTS TO EARTH HAND RESET FLAG SELF RESET CONTACTS CONTACT ARRANGEMENT: 3NO/0NC THREE CONTACTS, CASE SIZE E6 (4U HIGH) RATING: 1A AC

General technical data	
Rated current	1 A

Protection Functions	
protection function / three-pole tripping	Yes
product function / teleprotection scheme (ANSI 85)	Yes
protection function / differential protection, line (ANSI 87L)	Yes

Supply voltage	
line frequency	50 ... 60 Hz

Inputs / Outputs	
number of NC contacts	0
number of NO contacts	3
number of digital outputs / incl. signaling contact / maximum	3
number of current inputs / maximum	3

Mechanical Design

Subject to change without notice
© Copyright Siemens

width	155 mm
height	177 mm
depth	247 mm
frame size of enclosure	E6

Environmental conditions

ambient temperature / during operation / maximum	55 °C

Further information

Information- and Downloadcenter (catalogues, leaflets,...)
http://www.siemens.com/energy-automation

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2111-1DA30-0DB0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/7PG2111-1DA30-0DB0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2111-1DA30-0DB0

Tender specifications
http://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens