SIEMENS

Data sheet 5SK9011-8KK26

Circuit breaker for auxiliary circuits +overload+short-circuit release
Auxiliary current switch 1 NO+1 NC 1-pole, 4A

Model	
Product brand name	SENTRON
Product designation	Circuit breaker terminals
Design of the product	with overload and short-circuit release, auxiliary current switch with 1 NO and 1 NC
General technical data	
Number of poles	1
Tripping characteristic class	Other
Overvoltage category	3
Supply voltage	
Type of voltage	AC/DC
Current / at AC / rated value	4 A
Supply voltage / at AC / rated value	250 V
Operating voltage / at AC / at 50/60 Hz / rated value	250 V
Supply voltage frequency / rated value	60 Hz
Protection class	
Protection class IP	IP20
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	0.674 W
Product details	
Product feature / Touch protection	Yes
Product extension / can be installed / supplementary devices	Yes
Connections	
Connectable conductor cross-section / stranded	
• minimum	0.75 mm²
• maximum	1.5 mm²
Connectable conductor cross-section / finely stranded / with core end processing	
• minimum	1 mm²
• maximum	2.5 mm²
Mechanical Design	
Installation depth	92 mm

Subject to change without notice
© Copyright Siemens

Number of width units	1
Mounting position	any

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SK9011-8KK26

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SK9011-8KK26

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SK9011-8KK26

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
http://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens