SIEMENS

Data sheet 6AG1503-2CB00-2AA0

Product type designation

SIPLUS NET OLM/G11 V4.0
SIPLUS NET OLM/G11 V4.0 -25...+60°C based on 6GK1503-2CB00



Transfer rate	
Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Transfer rate / with PROFIBUS PA	45.45 kbit/s

Interfaces	
Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of electrical connections	
• for network components or terminal equipment	1
• for measuring device	1
• for signaling contact	1
• for redundant voltage supply	1
Type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply	-
• for power supply and signaling contact	5-pole terminal block
Number of optical interfaces / for fiber optic cable	1
Design of the optical interface / for fiber optic cable	BFOC port

Subject to change without notice
© Copyright Siemens

Optical data	
Damping ratio / of the FOC transmission link	
• for glass FOC with 50/125 µm / at 3 dB/km / maximum	10 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum	12 dB
propagation delay [bit]	6.5 bit
Connectable optical power relative to 1 mW	
• for glass FOC with 50/125 µm / at 3 dB/km	-15 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km	-13 dB
Optical sensitivity relating to 1 mW	
• for glass FOC with 50/125 µm / at 3 dB/km	-28 dB
• for glass FOC with 62.5/125 µm / at 3.5 dB/km	-28 dB
Wavelength	
• for glass FOC with 50/125 µm / compatible with interface / at 3 dB/km	860 nm
• for glass FOC with 62.5/125 µm / compatible with interface / at 3.5 dB/km	860 nm
Wire length	
• for glass FOC with 50/125 µm / at 3 dB/km / maximum	3 km
• for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum	3 km

Signal inputs/outputs	
Operating voltage / of the signaling contacts / at DC / Rated value	24 V
Operating current / of the signaling contacts / at DC / maximum	0.1 A

Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / at DC / Rated value	24 V
Supply voltage / at DC	18.8 ... 28.8 V
Product component / fusing at power supply input	Yes
Consumed current / at DC / at 24 V / maximum	0.2 A

Ambient conditions	
Ambient temperature	
• in horizontal mounting position / during operation	60 ... -25 °C
• during storage and transport	70 ... -40 °C
Installation altitude / at height above sea level / maximum	5000 m
Relative humidity	

Subject to change without notice
© Copyright Siemens

• with condensation / acc. to IEC 60068-2-38 / maximum	100 %
Chemical resistance / to commercially available cooling lubricants	Yes
Resistance to biologically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Coating / for equipped printed circuit board / acc. to EN 61086	Yes
Type of coating	
• protection against pollution according to EN 60664-3	Yes
Type of test / of the coating / acc. to MIL-I-46058C	Yes
Product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes
Protection class IP	IP40

Design, dimensions and weights

Design	compact
Width	39.5 mm
Height	112 mm
Depth	74.5 mm
Net weight	340 g
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Standards, specifications, approvals

Standard	
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-3
Certificate of suitability	EN 61000-6-2, EN 61000-6-5
• CE marking	Yes

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst

Subject to change without notice
© Copyright Siemens

• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	03/26/2020

Subject to change without notice
© Copyright Siemens