SIEMENS

Data sheet 6GK1551-2AA00

Product type designation

CP 5512
COMMUNICATION PROCESSOR CP 5512 PC CARD (CARDBUS, 32 BITS) FOR CONNECTION OF A PG OR NOTEBOOK TO PROFIBUS OR MPI



Transmission rate	
Transfer rate	
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Interfaces	
Number of electrical connections	
• at the 1st interface / acc. to PROFIBUS	1
Type of electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS 485)
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• 1 / from backplane bus	3.3 V
Relative symmetrical tolerance / at DC	
• at 3.3 V	5 %
Consumed current	
• 1 / from backplane bus / at DC / maximum	0.52 A
Active power loss	1.8 W

Changes preserved
© Copyright Siemens AG

Permitted ambient conditions	
Ambient temperature	
• during operation	5 ... 45 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP00

Design, dimensions and weight	
Module format	PC card Type II CardBus (32 bit)
Width	86 mm
Height	5 mm
Depth	54 mm
Net weight	130 g
Number of plug-in cards of same design / plug-in / per PC station	1
Number of units / Note	-

Performance data	

Performance data / open communication	
Software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50

Performance data / PROFIBUS DP	
Software / for DP master function / required	Yes, SOFTNET-PB DP
Service / as DP master	
• DPV0	Yes
• DPV1	No
• DPV2	No
Number of DP slaves / on DP master / usable	64
Amount of data	
• of the address area of the inputs / as DP master / total	7808 byte
• of the address area of the outputs / as DP master / total	7808 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	244 byte
Software / for DP slave function / required	Yes, SOFTNET-PB DP slave

Changes preserved
© Copyright Siemens AG

Service / as DP slave	
• DPV0	Yes
• DPV1	No
Amount of data	
• of the address area of the inputs / as DP slave / total	122 byte
• of the address area of the outputs / as DP slave / total	122 byte

Performance data / S7 communication	
Software / for S7 communication / required	Yes, SOFTNET-PB S7
Number of possible connections / for S7/PG communication / maximum	8

Performance data / multi-protocol mode	
Number of configurable connections / per PC station	207

Product functions / management, configuration	
Configuration software / required	Included in the scope of delivery of the required software product

Product functions / Diagnosis	
Product function	
• Port diagnostics	Yes

Standards, specifications, approvals	
Standard	
• for EMC	2004/108/EC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1
• for emitted interference	EN 61000-6-3, EN 61000-6-4
• for interference immunity	EN 61000-6-1, EN 61000-6-2
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes

Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Changes preserved
© Copyright Siemens AG

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	20.07.2015

Changes preserved
© Copyright Siemens AG